

Mabanol Argon Fleet 15W-40

High Performance Universal Engine Oil



Application

Mabanol Argon Fleet 15W-40 is a top-quality oil for universal, year-round application in mixed fleets. A single engine oil for all vehicles precludes any possibility of confusion, and guarantees economic stock maintenance.

Mabanol Argon Fleet 15W-40 is a high-performance universal engine oil for extended oil change intervals. The range of application covers not only the requirements of commercial vehicle and automobile diesel engines, but petrol engines as well. The high demands from modern, low-consumption engines for the fulfillment of the tightened EU standards for exhaust emissions are exceeded. In addition, Mabanol Argon Fleet 15W-40 meets the requirements of the ACEA A3/B3.

Properties

Mabanol Argon Fleet 15W-40 is a mineral oil based high-performance universal engine oil of SAE 15W-40 viscosity grade. These mineral oils are derived from the most modern refinery technologies, coupled with innovative additives matched to them thus ensuring that the demands of today's stringent standards are met. Its outstanding qualities include its excellent lubrication at high temperatures and the exceptional wear protection under all operating conditions.

Specifications

- SAE Grade 15W-40
- ACEA E7
- API SL/CI-4

Approvals

- MAN M 3275-1
- Volvo VDS-3
- Mack EO-N
- Renault VI RLD-2
- MTU MTL 5044 Typ 2

Recommended for

- MB-Sheet 228.3/229.1
- Caterpillar ECF-1a/ECF-2
- MTU DDC BR 2000/4000
- Mack EO-M Plus
- Cummins CES 20071/20072/20076/20077
- John Deere JDQ 78A
- ZF TE-ML 07C

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,881
Dyn. Viscosity at -20°C	ASTM D 5293	mPa s	6.800
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	106
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	14,3
Viscosity Index (VI)	ISO 2909		138
Flashpoint COC	ISO 2592	°C	235
Pourpoint	ISO 3016	°C	-33
Total base number	ISO 3771	mg KOH/g	9

Updated in June 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981