

Mabanol Argon Fleet 20W-50

Universal Engine Oil

Application

Mabanol Argon Fleet 20W-50 is a universal engine oil formulated to meet the stringent demands of manufacturers of petrol and diesel engines as well as respective turbo versions and heavy-duty vehicles. Hence, Mabanol Argon Fleet 20W-50 is a suitable oil for the year-round protection of mixed fleets and, as it can be universally applied, has a positive impact on economical storage.

Properties

Mabanol Argon Fleet 20W-50 is a mineral oil based universal engine oil. The viscosity formulation provides outstanding lubrication properties at high operating temperatures and is perfectly suitable for engines with a high mileage program.

Specifications

- SAE Grade 20W-50
- ACEA A3/B4 Performance
- API SL/CG-4

Recommended for

- MB-Sheet 228.3
- MAN 3275-1
- Volvo VDS

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,889
Dyn. Viscosity at -15°C	ASTM D 5293	mPa s	9.070
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	157
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	17,5
Viscosity Index (VI)	ISO 2909		122
Flashpoint COC	ISO 2592	°C	240
Pourpoint	ISO 3016	°C	-33

Updated in July 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981