

Mabanol Argon Fleet Classic 15W-40

Universal Engine Oil

Application

Mabanol Argon Fleet Classic 15W-40 is a universal engine oil formulated to meet the stringent demands of manufacturers of petrol and diesel engines. Therefore Mabanol Argon Fleet Classic 15W-40 is well-suited to the year-round protection of mixed fleets and, as it can be universally applied, has a positive impact on economical storage.

Properties

Mabanol Argon Fleet Classic 15W-40 is a universal engine oil produced from top-notch base oils and specially selected additives. The viscosity formulation provides outstanding lubrication properties at high operating temperatures and is perfectly suitable for engines with a high mileage program.

Specifications

- SAE Grade 15W-40
- API SF/CD

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,880
Dyn. Viscosity at -20°C	ASTM D 5293	mPa s	5.460
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	96
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	13,3
Viscosity Index (VI)	ISO 2909		140
Flashpoint COC	ISO 2592	°C	232
Pourpoint	ISO 3016	°C	-39
Total base number	ISO 3771	mg KOH/g	6

Updated in May 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981