

# Mabanol Argon Fleet Extra 10W-40

Universal Fuel Economy Engine Oil



## Application

Mabanol Argon Fleet Extra 10W-40 is a universal engine oil suitable for use in mixed vehicle fleets in various sectors (e.g. transport, agriculture and the construction industry).

This high performance engine oil can be confidently used for all types of petrol and diesel vehicles including those with turbocharged engines.

## Properties

Mabanol Argon Fleet Extra is a 10W-40 high performance engine oil. Synthetic components and modern additives make sure that its performance complies with high industry standards and also ensure that the properties listed below are covered. Mabanol Argon Fleet Extra

- offers year-round application
- ensures quick starts at low temperatures
- reduces cold start wear
- offers high temperature safety and cuts down fuel and oil consumption, thus reducing the environmental impact
- has a very good dirt-carrying capacity
- prevents sludge development
- extends service life of engines
- allows longer oil drain intervals

## Specifications

- SAE Grade 10W-40
- ACEA E7, A3/B4 Performance
- API CI-4/SL
- Global DHD-1

## Approvals

- MB-Approval 228.3/229.1
- MAN M 3275-1
- Volvo VDS-3
- Mack EO-N
- Renault VI RLD-2

## Recommended for

- Caterpillar ECF-1a/ECF-2
- MB-Sheet 235.28
- MTU MTL 5044 Type 2
- MTU DDC BR 2000 / 4000
- Cummins CES 20071/20072/20076/20077/20078
- Mack EO-M Plus
- Deutz DQC III-10
- Voith Retarder Type A
- DAF

## Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,873
Dyn. Viscosity at -25°C	ASTM D 5293	mPa s	6.650
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	98,6
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	14,6
Viscosity Index (VI)	ISO 2909		154
Flashpoint COC	ISO 2592	°C	230
Pourpoint	ISO 3016	°C	-36
Total base number	ISO 3771	mg KOH/g	10,6

Updated in Mai 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981