

Mabanol Argon Fleet Plus 20W-50

High Performance Universal Engine Oil



Application

Mabanol Argon Fleet Plus 20W-50 is a universal engine oil formulated to meet the stringent demands of manufacturers of petrol and diesel engines as well as respective turbo versions and heavy-duty vehicles. Hence, Mabanol Argon Fleet Plus 20W-50 is a suitable oil for the year-round protection of mixed fleets and, as it can be universally applied, has a positive impact on economical storage.

Properties

Mabanol Argon Fleet Plus 20W-50 is a mineral oil based universal engine oil. The viscosity formulation provides outstanding lubrication properties at high operating temperatures and is perfectly suitable for engines with a high mileage program.

Specifications

- SAE Grade 20W-50
- ACEA A3/B4/E7
- API CI-4/SL/CF
- Global DHD-1
- JASO DH-1

Recommended for

- MAN M 3275-1
- MB-Sheet 228.3/229.1
- Allison C-4
- Caterpillar ECF-1a/ECF-2
- Cummins CES 20076/20077/20078
- Detroit Diesel DDC 93K215
- Deutz DQC III-10
- Mack EO-M Plus
- MTU Type 2
- Renault VI RLD-2
- Volvo VDS-3

Data

	Test method	Unit	Value
Density at 15°C	DIN EN ISO 12185	g/cm ³	0,884
Kin. Viscosity at 40°C	DIN ISO 51562-2	mm ² /s	164,2
Kin. Viscosity at 100°C	DIN ISO 51562-2	mm ² /s	18,18
Viscosity Index (VI)	DIN ISO 2909		123
Flashpoint	ISO 2592	°C	258
Pourpoint	ASTM D 7346	°C	-36

Updated in June 2020

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981