

Mabanol Argon Truck Blue FE 10W-40

High Performance Engine Oil for Heavy-Duty Services (SHPD)



Application

Mabanol Argon Truck Blue FE 10W-40 is especially designed for economic use in low-exhaust engines with exhaust aftertreatment devices.

Mabanol Argon Truck Blue FE 10W-40 is a year-round high-performance motor oil which is perfectly suitable for heavy-duty engines required to meet Euro V and VI standards.

Properties

Mabanol Argon Truck Blue FE 10W-40 is a low-friction engine oil for turbo-charged commercial vehicles boasting a SHPD formulation (Super High Performance Diesel Engine Oil). The SAE 10W-40 year-round range of viscosities preferred by engine manufacturers is through the use of selected synthetic components and mineral base oils. SAE 10W cold viscosity ensures safer cold starts at very low outside temperatures (reduced wear in cold starting conditions) by ensuring that all vehicle components are sufficiently lubricated.

Specifications

- SAE Grade 10W-40
- ACEA E9
- API CJ-4/SN

Approvals

- MAN M 3575
- Renault VI RLD-3
- Mack EO-O Premium Plus
- Volvo VDS-4

Recommended for

- MB-Sheet 228.31
- Deutz DQC III-10 LA
- MTU MTL 5044 Typ 2.1
- MTU DDC BR 2000/4000
- Caterpillar ECF-1a/ECF-2/ECF-3
- Cummins CES 20081
- Detroit Diesel DDC 93K218

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,860
Dyn. Viscosity at -25°C	ASTM D 5293	mPa s	6.500
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	96,8
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	14,3
Viscosity Index (VI)	DIN ISO 2909		152
Flash point COC	DIN ISO 2592	°C	250
Pourpoint	DIN ISO 3016	°C	-39
Total base number	DIN ISO 3771	mgKOH/g	9,0

Updated in July 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981