

Mabanol Argon Truck Blue FE 15W-40

Low-SAPS High Performance Engine Oil for Heavy-Duty Vehicles

Application

Mabanol Argon Truck Blue FE 15W-40 is especially designed for use in heavy-duty vehicles equipped with turbocharger and intercooler.

Mabanol Argon Truck Blue FE 15W-40 is a year-round high-performance motor oil which is perfectly suitable for heavy-duty engines required to meet Euro IV, Euro V and Euro VI standards set by several engine manufacturers.

Properties

Mabanol Argon Truck Blue FE 15W-40 provides a Low-SAPS formulation that complies with the latest technical requirements laid down by various OEMs. The SAE grade 15W-40 year-round range of viscosities preferred by engine manufacturers is ensured thanks to the use of selected base oils and a fitting high-performance additive package.

Specifications

- SAE Grade 15W-40
- ACEA E9
- API CK-4 / SN
- Global DHD-1
- JASO DH-2

Recommended for

- MAN M 3575
- MB-Sheet 228.31
- Caterpillar ECF-2 / ECF-3
- Cummins CES 20081
- Deutz DQC III-10 LA
- Detroit Diesel DDC 93K218
- Ford WSS-M2C 171-F1
- John Deere JDQ 78X
- Mack EO-O Premium Plus
- MTU Type 2.1
- Renault VI RLD-3
- Volvo VDS-4

Data

	Test method	Unit	Value
Density at 15°C	DIN EN ISO 12185	g/cm ³	0,866
Dyn. Viscosity at -20°C	ASTM D 5293	mPa s	4.600
Kin. Viscosity at 40°C	DIN 51659-2	mm ² /s	100,8
Kin. Viscosity at 100°C	DIN 51659-2	mm ² /s	14,4
Viscosity Index (VI)	DIN ISO 2909		147
Flash point COC		°C	238
Pourpoint	ASTM D 7346	°C	-33
Total base number	ASTM D 2896	mgKOH/g	7,8

Updated in February 2022

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981