

Mabanol Argon Truck Blue Stellar 15W-40

Low-SAPS High Performance Engine Oil for Heavy-Duty Services

Application

Mabanol Argon Truck Blue Stellar 15W-40 is especially designed for use in heavy-duty vehicles equipped with turbocharger and intercooler.

Mabanol Argon Truck Blue Stellar 15W-40 is a year-round high-performance motor oil which is perfectly suitable for heavy-duty engines required to meet Euro V and VI standards set by several engine manufacturers.

Properties

Mabanol Argon Truck Blue Stellar 15W-40 is a low SAPS engine oil for turbocharged commercial vehicles based on modern synthesis technology. The SAE 15W-40 year-round range of viscosities preferred by engine manufacturers is given thanks to the use of selected synthetic components and mineral base oils. SAE 15W cold viscosity ensures safer cold starts at very low outside temperatures (reduced wear in cold starting conditions) by ensuring that all vehicle components are sufficiently lubricated.

Specifications

- SAE Grade 15W-40
- ACEA E9 / E7
- API CK-4 / CJ-4 / SN
- JASO DH-2

Recommended for

- MAN M 3775 / M 3575
- MB-Sheet 228.31
- Volvo VDS-4.5
- Deutz DQC III-18 LA
- Renault VI RLD-3
- Detroit Diesel DFS 93K222
- Caterpillar ECF-3
- Cummins CES 20086
- Mack EOS-4.5
- MTU MTL 5044Type 2.1
- Ford WSS-M2C171-F1
- Allison TES 439



Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,873
Dyn. Viscosity at -20°C	ASTM D 5293	mPa s	5.300
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	107,7
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	14,6
Viscosity Index (VI)	DIN ISO 2909		140
Flash point COC	DIN ISO 2592	°C	236
Pourpoint	DIN ISO 3016	°C	-42
Total base number	DIN ISO 3771	mgKOH/g	10,0

Updated in Oktober 2020

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981