

Mabanol Argon Truck FE Ultra 10W-40

High Performance Low Friction Engine Oil for Commercial Vehicles

Application

Mabanol Argon Truck FE Ultra 10W-40 is suitable for year-round use in heavily loaded heavy-duty vehicles as well as stationary diesel engines and can be confidently supplied to fleet operators.

It meets Euro IV and V standards and also complies with Euro VI requirements for Scania engines.

Properties

Mabanol Argon Truck FE Ultra 10W-40 is a high-performance engine oil suitable for use in heavy-duty vehicles. Smooth cold starts of engines at low ambient temperatures as well as improved protection against wear and corrosion are ensured by virtue of its low temperature viscosity. Operations conducted under extreme conditions are handled well thanks to the high-temperature viscosity attributes.

Mabanol Argon Truck FE Ultra 10W-40 is an economical heavy-duty engine oil which features improved fuel economy properties (reduced fuel and lube consumption) as well as longest oil drain intervals even when biofuel is used.

Specifications

- SAE Grade 10W-40
- ACEA E4 / E7
- API CI-4

Approval

- Scania LDF-3

Recommended for

- Volvo VDS-3
- Renault VI RLD-2
- Mack EO-N / EO-N-PP-03
- MB-Sheet 228.5
- MAN M 3277
- Cummins CES 20077 / 20078
- DAF
- Deutz DQC IV-18
- MTU MTL 5044 Typ 3



Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,865
Dyn. Viscosity at -25°C	ASTM D 5293	mPa s	5.950
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	97,4
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	14,4
Viscosity Index (VI)	DIN ISO 2909		152
Flash point COC	DIN ISO 2592	°C	236
Pourpoint	DIN ISO 3016	°C	-45
Total base number	DIN ISO 3771	mgKOH/g	15,9

Updated in September 2020

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981