



Mabanol Brake Fluid DOT-4

Synthetic Brake Fluid

Application

Mabanol Brake Fluid DOT-4 is suitable for use in hydraulic brake systems (disc or drum types) which require the specification DOT-4.

Properties

Mabanol Brake Fluid DOT-4 is a synthetic brake fluid. The performance covers properties such as excellent oxidation stability, protection against corrosion, a good low-temperature viscosity as well as an optimum wet boiling point.

Specifications

- FMVSS 116 DOT 4
- SAE J1703
- ISO 4925

Data

	Test method	Unit	Value
Density at 20°C	DIN 51 757	g/cm ³	1,04
Kin. Viscosity at -40°C	ASTM D 445	mm ² /s	1315
Kin. Viscosity at 100°C	ASTM D 445	mm ² /s	2,34
pH-value	SAE J 1703	pH	8,53
Evaporation		%w/w	56
Dry boiling point	FMVSS 116	°C	270
Wet boiling point	FMVSS 116	°C	163

Updated in July 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 3819 0000

Mabanol GmbH & Co. KG, Koreastraße 7, 20457 Hamburg, Deutschland

Telefon +49 (0)40 36809988, Telefax +49 (0)40 36901781,
Email: info@mabanol.com, Internet: www.mabanol.com