according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 2 Feb 2023 Print date: 2 Feb 2023 Version: 1



Mabanol Cut Lub 14 G HP

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Trade name/designation:

Mabanol Cut Lub 14 G HP

UFI:

672Q-7FP5-1671-7VN3

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Metalworking fluids

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Mabanol GmbH & Co. KG Koreastraße 7 20457 Hamburg Germany Telephone: 0049 (0) 40 36809988 E-mail: info@mabanol.com Website: www.mabanol.com

E-mail (competent person): giznord@giz-nord.de

1.4. Emergency telephone number

Giftinformationszentrale Göttingen , 24h: 0049 (0) 551 1 92 40

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

 Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:



according to Regulation (EC) No. 1907/2006 (REACH) **Revision date:** 2 Feb 2023

Print date: 2 Feb 2023 Version: 1



Page 2/10

Mabanol Cut Lub 14 G HP

Hazard components for labelling:

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts; C18-C50 branched, cyclic and linear hydrocarbons – Distillates

Hazard statements for health hazards			
H304 May be fatal if swallowed and enters airways.			
Supplemental hazard information			
EUH208	Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts. May produce an allergic reaction.		

Precautionary statements Response

P301 + P310IF SWALLOWED: Immediately call a POISON CENTER/doctor/Emergency telephone number.P331Do NOT induce vomiting.

Precautionary statements Storage

P405 Store locked up.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Mixture of base oils and additives.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 848301-69-9 EC No.: 482-220-0 REACH No.: 01-0000020163-82	C18-C50 branched, cyclic and linear hydrocarbons - Distillates Asp. Tox. 1 (H304) Danger	75 - < 80 weight-%
CAS No.: 68584-23-6 EC No.: 271-529-4 REACH No.: 01-2119492627-25	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts Skin Sens. 1B (H317) ↔ Warning Specific concentration limit (SCL) Skin Sens. 1B; H317: C ≥ 10%	0.1 - < 0.5 weight-%
CAS No.: 128-37-0 EC No.: 204-881-4 REACH No.: 01-2119565113-46	2,6-di-tert-butyl-p-cresol Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410) ↓ Warning M-factor (acute): 1 M-factor (chronic): 1	< 0.25 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

When in doubt or if symptoms are observed, get medical advice.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. Where appropriate artificial ventilation. In case of respiratory tract irritation, consult a physician.

In case of skin contact:

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 Feb 2023 Print date: 2 Feb 2023 Version: 1



Page 3/10

Mabanol Cut Lub 14 G HP

Following ingestion:

Do NOT induce vomiting. Call a physician immediately. Rinse mouth thoroughly with water. Observe risk of aspiration if vomiting occurs.

Self-protection of the first aider:

No direct artificial respiration to be given by first aider.

4.2. Most important symptoms and effects, both acute and delayed Cough. Respiratory complaints. Dyspnoea. Fever. Pneumonia.

Symptoms can occur only after several hours.

4.3. Indication of any immediate medical attention and special treatment needed First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam. Extinguishing powder. Carbon dioxide (CO2). Water spray jet. Water mist.

Unsuitable extinguishing media:

Strong water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous combustion products:

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide. Nitrogen oxides (NOx)..

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Ventilate affected area. Remove all sources of ignition.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Cover drains. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Cover drains. Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control. Prevent spread over a wide area (e.g. by containment or oil barriers). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Ventilate affected area. Clean contaminated articles and floor according to the environmental legislation.

according to Regulation (EC) No. 1907/2006 (REACH) **Revision date:** 2 Feb 2023

Print date: 2 Feb 2023 Version: 1



Page 4/10

Mabanol Cut Lub 14 G HP

6.4. Reference to other sections

Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8). Use only in well-ventilated areas. Handle and open container with care. Always close containers tightly after the removal of product. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking.

Fire prevent measures:

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.

Environmental precautions:

Shafts and sewers must be protected from entry of the product. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin. Wash hands before breaks and after work. Apply skin care products after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Used working clothes should not be worn outside the work area. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place. Protect containers against damage. Only use containers specifically approved for the substance/product. Floors should be impervious, resistant to liquids and easy to clean.

Hints on storage assembly:

Do not store together with: Food and feedingstuffs.

Keep away from: Oxidizing agent.

Storage class (TRGS 510, Germany): 10 – Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Recommended storage temperature: 5 - 40°C. Protect against: Frost. Heat. UV-radiation/sunlight. Water. Humidity. storage stability: max. 24 month(s).

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
TRGS 900 (DE) from 1 Jul 2012	2,6-di-tert-butyl-p-cresol CAS No.: 128-37-0 EC No.: 204-881-4	 10 mg/m³ 40 mg/m³ (Aerosol und Dampf, einatembare Fraktion) DFG, Y, 11

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 2 Feb 2023 Print date: 2 Feb 2023 Version: 1



Page 5/10

Mabanol Cut Lub 14 G HP

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	 DNEL type Exposure route
2,6-di-tert-butyl-p-cresol CAS No.: 128-37-0 EC No.: 204-881-4	5.8 mg/m ³	 DNEL worker Long-term - inhalation, systemic effects
2,6-di-tert-butyl-p-cresol CAS No.: 128-37-0 EC No.: 204-881-4	8.3 mg/kg	 DNEL worker Long-term - dermal, systemic effects
Substance name	PNEC Value	① PNEC type
2,6-di-tert-butyl-p-cresol CAS No.: 128-37-0 EC No.: 204-881-4	0.004 mg/L	 PNEC aquatic, freshwater
2,6-di-tert-butyl-p-cresol CAS No.: 128-37-0 EC No.: 204-881-4	0.0004 mg/L	① PNEC aquatic, marine water
2,6-di-tert-butyl-p-cresol CAS No.: 128-37-0 EC No.: 204-881-4	100 mg/L	① PNEC sewage treatment plant
2,6-di-tert-butyl-p-cresol CAS No.: 128-37-0 EC No.: 204-881-4	1.29 mg/kg	${f 1}$ PNEC sediment, freshwater

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection (EN 166).

Skin protection:

Tested protective gloves must be worn (EN ISO 374).

Wearing time with permanent contact:

Suitable material: NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber). PVA (Polyvinyl alcohol). Thickness of the glove material: 0,70 mm. Breakthrough time:: > 480 min.

Wearing time with occasional contact (splashes):

Suitable material: NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber). PVA (Polyvinyl alcohol). Thickness of the glove material: 0,40 mm. Breakthrough time:: > 30 min.

Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable protective clothing: flame-resistant.

Respiratory protection:

Usually no personal respirative protection necessary.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection necessary at: exceeding exposure limit values. insufficient ventilation. aerosol or mist formation.

8.2.3. Environmental exposure controls

No data available

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 2 Feb 2023 Print date: 2 Feb 2023

Version: 1 Page 6/10

Mabanol Cut Lub 14 G HP

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid **Odour:** not determined

Colour: brown

Safety relevant basis data

Parameter	Value at °	at °C	1 Method
			② Remark
рН	not determined		
Melting point	not determined		
Freezing point	not determined		
Initial boiling point and boiling range	> 220 °C		② 1013 hPa
Decomposition temperature	not determined		
Flash point	196 °C		1 EN ISO 2592
Evaporation rate	not determined		
Auto-ignition temperature	> 220 °C		
Upper/lower flammability or explosive limits	0.6 - 6.5 Vol-%		
Vapour pressure	not determined		
Vapour density	not determined		
Density	0.847 g/cm ³	15 °C	1 DIN EN ISO 12185
Relative density	not determined		
Bulk density	not determined		
Water solubility	practically insoluble	20 °C	
Partition coefficient: n-octanol/water	not determined		
Dynamic viscosity	not determined		
Kinematic viscosity	13 mm²/s	40 °C	1 EN ISO 3104

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 2 Feb 2023 Print date: 2 Feb 2023



Version: 1 Page 7/10

Mabanol Cut Lub 14 G HP

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
C18-C50 branched, cyclic and linear hydrocarbons - Distillates CAS No.: 848301-69-9 EC No.: 482-220-0
LD ₅₀ oral: >5,000 mg/kg (Rat)
LD ₅₀ dermal: >5,000 mg/kg (Rabbit)
LC ₅₀ Acute inhalation toxicity (vapour): >5 mg/L 4 h (Rat)
Acute oral toxicity:
No data available. The statement is derived from the properties of the single components. Based on available data, the classification criteria are not met.
Acute dermal toxicity:
Based on available data, the classification criteria are not met.
Acute inhalation toxicity:
Based on available data, the classification criteria are not met.
Skin corrosion/irritation:
Based on available data, the classification criteria are not met.
Serious eye damage/irritation: Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation: May cause sensitization by skin contact.
Germ cell mutagenicity:
Based on available data, the classification criteria are not met.
Carcinogenicity:
Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.
STOT-single exposure: Based on available data, the classification criteria are not met.
STOT-repeated exposure:
Based on available data, the classification criteria are not met.
Aspiration hazard:
May be fatal if swallowed and enters airways.
For viscosity data, see section 9.
Additional information:
Frequently or prolonged contact with skin may cause dermal irritation.
11.2. Information on other hazards
Endocrine disrupting properties: No information available.

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity:

Harmless to aquatic organisms up to the tested concentration.

Additional ecotoxicological information:

There are no data available on the mixture itself. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3). Do not allow uncontrolled discharge of product into the environment.

12.2. Persistence and degradability

Biodegradation:

Moderately/partially biodegradable.

Additional information:

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 2 Feb 2023 Print date: 2 Feb 2023 Version: 1



Page 8/10

Mabanol Cut Lub 14 G HP

12.3. Bioaccumulative potential

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

12 01 07 * mineral-based machining oils free of halogens (except emulsions and solutions) *: Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal. Dispose of waste according to applicable legislation.

Appropriate disposal / Package:

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Handle contaminated packages in the same way as the substance itself. Dispose of waste according to applicable legislation.

13.2. Additional information

Never use pressure to empty container.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or	ID number	·	
No dangerous good in sense of these transport regulations.			
14.2. UN proper ship	ping name		
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport haza	rd class(es)	<u>.</u>	
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental	hazards		
not relevant	not relevant	not relevant	not relevant
14.6. Special precau	tions for user		
not relevant	not relevant	not relevant	not relevant

according to Regulation (EC) No. 1907/2006 (REACH) Revision date: 2 Feb 2023 Print date: 2 Feb 2023



Version: 1 Page 9/10

Mabanol Cut Lub 14 G HP

14.7. Maritime transport in bulk according to IMO instruments not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Use restriction according to REACH annex XVII, no.: 3. 75.

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: This product is not assigned to a hazard category.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]: No information available. Observe in addition any national regulations!

15.1.2. National regulations

[DE] National regulations

Störfallverordnung (12. BlmschV)

for substances contained in the product:

This product is not assigned to a hazard category.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:

Weight fraction (Number 5.2.5. I): <5 %.

No flammable liquid according to BetrSichV.

Water hazard class

WGK:

1 - schwach wassergefährdend

Remark:

Self-classification (mixture; calculation rule).

15.2. Chemical Safety Assessment

No information available.

15.3. Additional information

Water hazard class (WGK): 1 (slightly hazardous to water).

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: Accord européen sur le transport des marchandises dangereuses par Route (International Carriage of Dangerous Goods by Road)

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC₅₀: Lethal concentration, 50 percent

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 2 Feb 2023 Print date: 2 Feb 2023 Version: 1



Page 10/10

Mabanol Cut Lub 14 G HP

LD₅₀: Lethal dose, 50 percent NIOSH: National Institute of Occupational Safety and Health NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level NTP: National Toxicology Program N/A: not applicable OEL: Occupational Exposure imit (Arbeitsplatzgrenzwert) OSHA: Occupational Safety and Health Administration PEL: permissible exposure limit (Zulässiger Expositionsgrenzwert) PBT: persistent bioaccumulative toxic PNEC: predicted no effect concentration REL: Recommended exposure limit (Empfohlene Expositionsgrenze) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) SARA: Superfund Amendments and Reauthorization Act STEL: Short Term Exposure Limit (Kurzzeitgrenzwert) (15 min) SVHC: substance of very high concern TLV: Threshold Limit Values (Schwellwert Grenzwerte) TRGS Technische Regeln für Gefahrstoffe TSCA: Toxic Substances Control Act TWA: Time Weighted Average (Zeitlich gewichteter Mittelwert) (8 h) VOC: Volatile Organic Compounds VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe WGK: Wassergefährdungsklasse 16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (Asp. Tox. 1)	H304: May be fatal if swallowed and enters airways.	

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements		
H304 May be fatal if swallowed and enters airways.		
H317 May cause an allergic skin reaction.		
H400 Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.	

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.