

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 1/17

## Mabanol Cut Lub 15

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name/designation:

Mabanol Cut Lub 15

UFI:

5DRY-JJT3-1A74-8S5Q

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Metalworking fluids

#### \* 1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Mabanol GmbH & Co. KG

Am Strandkai 1

20457 Hamburg

Germany

Telephone: 0049 (0) 40 36809988

E-mail: info@mabanol.com

Website: www.mabanol.com

E-mail (competent person): giznord@giz-nord.de

#### \* 1.4. Emergency telephone number

Giftinformationszentrale Göttingen , 24h: 0049 (0) 551 1 92 40

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard ( <i>Asp. Tox. 1</i> )	H304: May be fatal if swallowed and enters airways.	

#### \* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



**GHS08**

Health hazard

Signal word: Danger

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 2/17

## Mabanol Cut Lub 15

### Hazard components for labelling:

Distillates (petroleum), solvent-dewaxed light paraffinic

#### Hazard statements for health hazards

H304	May be fatal if swallowed and enters airways.
------	---

#### Precautionary statements Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P331	Do NOT induce vomiting.

#### Precautionary statements Storage

P405	Store locked up.
------	------------------

#### Precautionary statements Disposal

P501	Dispose of contents/container to Dispose of waste according to applicable legislation..
------	---

### Additional information:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

### 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

### \* 3.2. Mixtures

#### Additional information:

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

#### Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-56-9 EC No.: 265-159-2 REACH No.: 01-2119480132-48	<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> Asp. Tox. 1 (H304) Danger <b>Acute Toxicity Estimate</b> ATE (oral) > 5,000 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, dust/mist) > 5.53 mg/L	87 - < 95 weight-%
CAS No.: 128-39-2 EC No.: 204-884-0 REACH No.: 01-2119490822-33	<b>2,6-di-tert-butylphenol</b> Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410), Skin Irrit. 2 (H315) Warning <b>Acute Toxicity Estimate</b> ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg	0.1 - < 0.15 weight-%
CAS No.: 104-76-7 EC No.: 203-234-3 REACH No.: 01-2119487289-20	<b>2-ethylhexan-1-ol</b> Acute Tox. 4 (H332), Eye Irrit. 2 (H319), STOT SE 3 (H335), Skin Irrit. 2 (H315) Warning <b>Acute Toxicity Estimate</b> ATE (oral) 2,047 mg/kg ATE (dermal) > 3,000 mg/kg ATE (inhalation, vapour) 11 mg/L ATE (inhalation, dust/mist) 4.3 mg/L	< 0.05 weight-%

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 3/17

## Mabanol Cut Lub 15

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 108-88-3 EC No.: 203-625-9 Index No.: 601-021-00-3 REACH No.: 01-2119471310-51	<b>toluene</b> Asp. Tox. 1 (H304), Flam. Liq. 2 (H225), Repr. 2 (H361d***), STOT RE 2 (H373**), STOT SE 3 (H336), Skin Irrit. 2 (H315) Danger <b>Acute Toxicity Estimate</b> ATE (oral) > 5,000 mg/kg ATE (dermal) > 5,000 mg/kg ATE (inhalation, vapour) 28.1 mg/L	< 0.05 weight-%
CAS No.: 108-95-2 EC No.: 203-632-7 Index No.: 604-001-00-2	<b>phenol</b> Acute Tox. 3 (H331, H311, H301), Muta. 2 (H341), STOT RE 2 (H373**), Skin Corr. 1B (H314) Danger <b>Specific concentration limit (SCL)</b> Skin Corr. 1B; H314: C ≥ 3% Skin Irrit. 2; H315: 1% ≤ C < 3% Eye Dam. 1; H318: C ≥ 3% Eye Irrit. 2; H319: 1% ≤ C < 3% <b>Acute Toxicity Estimate</b> ATE (oral) 282 mg/kg ATE (dermal) 660 mg/kg ATE (inhalation, vapour) 3 mg/L ATE (inhalation, dust/mist) > 0.9 mg/L	< 0.05 weight-%

Full text of H- and EUH-phrases: see section 16.

## SECTION 4: First aid measures

### \* 4.1. Description of first aid measures

#### General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

#### Following inhalation:

Remove casualty to fresh air and keep warm and at rest. When in doubt or if symptoms are observed, get medical advice.

#### In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, consult a physician.

#### After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

#### Following ingestion:

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Observe risk of aspiration if vomiting occurs. Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

Observe risk of aspiration if vomiting occurs.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media:

Sand. Foam. Carbon dioxide (CO<sub>2</sub>). Extinguishing powder.  
In case of major fire and large quantities: Water spray jet. Water mist.

#### Unsuitable extinguishing media:

Full water jet.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 4/17

## Mabanol Cut Lub 15

### 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

#### Hazardous combustion products:

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Sulphur dioxide (SO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).

### 5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Wear a self-contained breathing apparatus and chemical protective clothing.

### 5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

##### Personal precautions:

Use personal protection equipment. Ventilate affected area. Special danger of slipping by leaking/spilling product.

#### 6.1.2. For emergency responders

##### Personal protection equipment:

Personal protection equipment: see section 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil.

### 6.3. Methods and material for containment and cleaning up

#### For cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Protective measures

#### Advices on safe handling:

Wear personal protection equipment (refer to section 8). Avoid: generation/formation of aerosols. Generation/formation of mist.

#### Fire prevent measures:

Usual measures for fire prevention. Keep away from sources of ignition - No smoking. Fire class: B (Fires of liquids or liquid turning substances).

#### Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin. Wash hands before breaks and after work. Apply skin care products after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Used working clothes should not be worn outside the work area. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 5/17

## Mabanol Cut Lub 15

### Hints on storage assembly:

Do not store together with: Gas. Explosives. P8 OXIDISING LIQUIDS AND SOLIDS. Radioactive substances. Infectious substances.

**Storage class (TRGS 510, Germany):** 10 - Combustible liquids that cannot be assigned to any of the above storage classes

### Further information on storage conditions:

Temperature control required. Protect from direct sunlight. Keep container tightly closed. Do not allow contact with air.

### 7.3. Specific end use(s)

No data available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE) from 20 Apr 2023	<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	① 1 ppm (5.4 mg/m <sup>3</sup> ) ⑤ (Aerosol und Dampf) EU, Y, 11
IOELV (EU) from 21 Feb 2017	<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	① 1 ppm (5.4 mg/m <sup>3</sup> )
TRGS 900 (DE) from 2 Jul 2021	<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	① 50 ppm (190 mg/m <sup>3</sup> ) ② 100 ppm (380 mg/m <sup>3</sup> ) ⑤ (kann über die Haut aufgenommen werden) DFG, EU, H, Y
IOELV (EU)	<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	① 50 ppm (192 mg/m <sup>3</sup> ) ② 100 ppm (384 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)
TRGS 900 (DE) from 1 May 2010	<b>phenol</b> CAS No.: 108-95-2 EC No.: 203-632-7	① 2 ppm (8 mg/m <sup>3</sup> ) ② 4 ppm (16 mg/m <sup>3</sup> ) ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden) EU, H, 11
IOELV (EU) from 17 Dec 2009	<b>phenol</b> CAS No.: 108-95-2 EC No.: 203-632-7	① 2 ppm (8 mg/m <sup>3</sup> ) ② 4 ppm (16 mg/m <sup>3</sup> ) ⑤ (may be absorbed through the skin)

#### 8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
TRGS 903 (DE) from 10 Oct 2024	<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	1.5 mg/L	① o-Kresol ② Urin ③ bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten
TRGS 903 (DE) from 10 Oct 2024	<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	600 µg/L	① Toluol ② Blut ③ unmittelbar nach Exposition

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 6/17

## Mabanol Cut Lub 15

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
TRGS 903 (DE) from 28 Mar 2019	<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	75 µg/L	① Toluol ② Urin ③ Expositionsende bzw. Schichtende
TRGS 903 (DE) from 19 Sept 2013	<b>phenol</b> CAS No.: 108-95-2 EC No.: 203-632-7	120 mg/g Creatinin	① Phenol ② Urin ③ Expositionsende bzw. Schichtende
BLV (EU) from 1 Jun 2014	<b>phenol</b> CAS No.: 108-95-2 EC No.: 203-632-7	120 mg/g creatinine	① phenol ② urine ③ no restriction

### 8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2	2.73 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2	5.58 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects
<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2	1.19 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, local effects
<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2	0.97 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2	0.74 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	70.61 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	20.9 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	11.25 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	6.75 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	6.75 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	12.8 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	2.3 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 7/17

## Mabanol Cut Lub 15

Substance name	DNEL value	① DNEL type ② Exposure route
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	53.2 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	26.6 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, local effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	53.2 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, local effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	26.6 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, local effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	23 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	11.4 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	1.1 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	192 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, systemic effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	56.5 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, systemic effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	384 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, systemic effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	226 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, systemic effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	192 mg/m <sup>3</sup>	① DNEL worker ② Long-term - inhalation, local effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	56.5 mg/m <sup>3</sup>	① DNEL Consumer ② Long-term - inhalation, local effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	384 mg/m <sup>3</sup>	① DNEL worker ② Acute - inhalation, local effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	226 mg/m <sup>3</sup>	① DNEL Consumer ② Acute - inhalation, local effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	384 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	226 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 8/17

## Mabanol Cut Lub 15

Substance name	DNEL value	① DNEL type ② Exposure route
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	8.13 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Substance name	PNEC Value	① PNEC type
<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2	9.33 mg/kg	① PNEC secondary poisoning
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	0.001 mg/L	① PNEC aquatic, freshwater
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	0.0001 mg/L	① PNEC aquatic, marine water
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	10 mg/kg	① PNEC sewage treatment plant
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	0.317 mg/kg	① PNEC sediment, freshwater
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	0.0317 mg/kg	① PNEC sediment, marine water
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	0.679 mg/kg	① PNEC soil
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0	60 mg/kg	① PNEC secondary poisoning
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	0.017 mg/L	① PNEC aquatic, freshwater
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	0.002 mg/L	① PNEC aquatic, marine water
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	10 mg/L	① PNEC sewage treatment plant
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	0.284 mg/kg	① PNEC sediment, freshwater
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	0.028 mg/kg	① PNEC sediment, marine water
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	0.047 mg/kg	① PNEC soil
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3	55 mg/kg	① PNEC secondary poisoning
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	0.68 mg/L	① PNEC aquatic, freshwater
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	0.68 mg/L	① PNEC aquatic, marine water

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 9/17

## Mabanol Cut Lub 15

Substance name	PNEC Value	① PNEC type
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	13.61 mg/L	① PNEC sewage treatment plant
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	16.39 mg/kg	① PNEC sediment, freshwater
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	16.39 mg/kg	① PNEC sediment, marine water
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9	2.89 mg/kg	① PNEC soil

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Provide adequate ventilation.

#### 8.2.2. Personal protection equipment



##### Eye/face protection:

Safety goggles with side protection. In case of increased risk add protective face shield. DIN EN 166.

##### Skin protection:

Tested protective gloves must be worn (EN ISO 374).

Suitable material: NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber). FKM (fluoro rubber).

Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable protective clothing: flame-resistant.

##### Respiratory protection:

Usually no personal respiratory protection necessary.

Respiratory protection necessary at: exceeding exposure limit values. aerosol or mist formation. Suitable respiratory protection apparatus: Filtering device (full mask or mouthpiece) with filter: A2, A2/P2, ABEK.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

#### 8.2.3. Environmental exposure controls

No information available.

### \* 8.3. Additional information

Air limit values:

Possibility of exposure to Aerosol (Mineral oil)

Limit value (TLV-TWA ) = 5 mg/ m<sup>3</sup> - Source: ACGIH

Limit value (TLV-STEL ) = 10 mg/ m<sup>3</sup> - Source: ACGIH

## SECTION 9: Physical and chemical properties

### \* 9.1. Information on basic physical and chemical properties

#### Appearance

**Physical state:** Liquid

**Odour:** not determined

**Colour:** clear

**flammability:** No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 10/17

## Mabanol Cut Lub 15

### Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	No data available		
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	No data available		
Flash point	190 °C		① DIN ISO 2592
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	No data available		
Vapour density	No data available		
Density	0.86 g/cm <sup>3</sup>	15 °C	① DIN 51757
Bulk density	not applicable		
Water solubility	Immiscible		
Dynamic viscosity	No data available		
Kinematic viscosity	15.6 mm <sup>2</sup> /s	40 °C	① EN ISO 3104
Pour point	-33 °C		① ASTM D 5985

### 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No information available.

### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

### 10.4. Conditions to avoid

No information available.

### 10.5. Incompatible materials

Oxidising agent, strong.

### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

## SECTION 11: Toxicological information

### \* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicological information

##### Acute Toxicity Estimate for Mixtures

ATE (oral): >2,000 mg/kg

ATE (dermal): >2,000 mg/kg

ATE (inhalation, vapour): >20 mg/L

ATE (inhalation, dust/mist): >5 mg/L

Distillates (petroleum), solvent-dewaxed light paraffinic CAS No.: 64742-56-9 EC No.: 265-159-2

LD<sub>50</sub> oral: >5,000 mg/kg (Rat)

LD<sub>50</sub> dermal: >5,000 mg/kg (Rabbit)

LC<sub>50</sub> Acute inhalation toxicity (dust/mist): >5.53 mg/L 4 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 11/17

## Mabanol Cut Lub 15

<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0
<b>LD<sub>50</sub> oral:</b> >5,000 mg/kg (Rat) OECD 401
<b>LD<sub>50</sub> dermal:</b> >2,000 mg/kg (Rat)
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3
<b>ATE (inhalation, vapour):</b> 11 mg/L
<b>LD<sub>50</sub> oral:</b> 2,047 mg/kg (Rat) OECD 401
<b>LD<sub>50</sub> dermal:</b> >3,000 mg/kg (Rat) OECD 402
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> 4.3 mg/L 4 h (Rat) OECD 403
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9
<b>LD<sub>50</sub> oral:</b> >5,000 mg/kg (Rat)
<b>LD<sub>50</sub> dermal:</b> >5,000 mg/kg (Rabbit)
<b>LC<sub>50</sub> Acute inhalation toxicity (vapour):</b> 28.1 mg/L 4 h (Rat) OECD 403
<b>phenol</b> CAS No.: 108-95-2 EC No.: 203-632-7
<b>ATE (inhalation, vapour):</b> 3 mg/L
<b>LD<sub>50</sub> oral:</b> 282 mg/kg (Mouse)
<b>LD<sub>50</sub> dermal:</b> 660 mg/kg (Rat)
<b>LC<sub>50</sub> Acute inhalation toxicity (dust/mist):</b> >0.9 mg/L 4 h (Rat) OECD 403

### Acute oral toxicity:

Based on available data, the classification criteria are not met.

### Acute dermal toxicity:

Based on available data, the classification criteria are not met.

### Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

### Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

### Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

### Carcinogenicity:

Based on available data, the classification criteria are not met.

### Reproductive toxicity:

Based on available data, the classification criteria are not met.

### STOT-single exposure:

Based on available data, the classification criteria are not met.

### STOT-repeated exposure:

Based on available data, the classification criteria are not met.

### Aspiration hazard:

May be fatal if swallowed and enters airways.

### Additional information:

Frequently or prolonged contact with skin may cause dermal irritation.

## 11.2. Information on other hazards

### Endocrine disrupting properties:

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 12/17

## Mabanol Cut Lub 15

### SECTION 12: Ecological information

#### \* 12.1. Toxicity

<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2
<b>LC<sub>50</sub>:</b> >100 mg/L 4 d (fish, Pimephales promelas (fathead minnow))
<b>EC<sub>50</sub>:</b> >10,000 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
<b>NOEC:</b> 10 mg/L 21 d (crustaceans, Daphnia magna (Big water flea))
<b>ErC<sub>50</sub>:</b> >100 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0
<b>LC<sub>50</sub>:</b> 1.4 mg/L 4 d (fish, Pimephales promelas (fathead minnow))
<b>EC<sub>50</sub>:</b> 0.45 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
<b>NOEC:</b> 0.023 mg/L 21 d (crustaceans, Daphnia magna (Big water flea))
<b>ErC<sub>50</sub>:</b> 1.4 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3
<b>LC<sub>50</sub>:</b> 17.1 mg/L 4 d (fish, Leuciscus idus (golden orfe))
<b>EC<sub>50</sub>:</b> 39 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
<b>ErC<sub>50</sub>:</b> 11.5 mg/L 3 d (Algae/water plant, Scenedesmus subspicatus)
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9
<b>LC<sub>50</sub>:</b> 5.5 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
<b>EC<sub>50</sub>:</b> 3.78 mg/L 2 d (crustaceans, Ceriodaphnia spec)
<b>phenol</b> CAS No.: 108-95-2 EC No.: 203-632-7
<b>LC<sub>50</sub>:</b> 21.93 mg/L 4 d (fish, Poecilia reticulata (Guppy))
<b>EC<sub>50</sub>:</b> 3.1 mg/L 2 d (crustaceans, Ceriodaphnia spec)
<b>ErC<sub>50</sub>:</b> 61.1 mg/L 4 d (Algae/water plant, Pseudokirchneriella subcapitata)

#### Assessment/classification:

Based on available data, the classification criteria are not met.

#### 12.2. Persistence and degradability

<b>Distillates (petroleum), solvent-dewaxed light paraffinic</b> CAS No.: 64742-56-9 EC No.: 265-159-2
<b>Biodegradation:</b> —
<b>Remark:</b> Not readily biodegradable (according to OECD criteria)
<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0
<b>Biodegradation:</b> —
<b>Remark:</b> Not readily biodegradable (according to OECD criteria)
<b>2-ethylhexan-1-ol</b> CAS No.: 104-76-7 EC No.: 203-234-3
<b>Biodegradation:</b> —
<b>Remark:</b> Readily biodegradable (according to OECD criteria).
<b>toluene</b> CAS No.: 108-88-3 EC No.: 203-625-9
<b>Biodegradation:</b> —
<b>Remark:</b> Readily biodegradable (according to OECD criteria).
<b>phenol</b> CAS No.: 108-95-2 EC No.: 203-632-7
<b>Biodegradation:</b> —
<b>Remark:</b> Readily biodegradable (according to OECD criteria).

#### Additional information:

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

#### \* 12.3. Bioaccumulative potential

<b>2,6-di-tert-butylphenol</b> CAS No.: 128-39-2 EC No.: 204-884-0
<b>Log K<sub>ow</sub>:</b> 4.5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 13/17

## Mabanol Cut Lub 15

**2-ethylhexan-1-ol** CAS No.: 104-76-7 EC No.: 203-234-3

**Log K<sub>ow</sub>**: 2.9

**toluene** CAS No.: 108-88-3 EC No.: 203-625-9

**Log K<sub>ow</sub>**: 2.73

**Bioconcentration factor (BCF)**: 90 Species: Leuciscus idus (golden orfe)

**phenol** CAS No.: 108-95-2 EC No.: 203-632-7

**Log K<sub>ow</sub>**: 1.47

**Bioconcentration factor (BCF)**: 17.5 Species: Danio rerio (zebrafish)

### Accumulation / Evaluation:

No indication of bioaccumulation potential.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

**Distillates (petroleum), solvent-dewaxed light paraffinic** CAS No.: 64742-56-9 EC No.: 265-159-2

**Results of PBT and vPvB assessment:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**2,6-di-tert-butylphenol** CAS No.: 128-39-2 EC No.: 204-884-0

**Results of PBT and vPvB assessment:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**2-ethylhexan-1-ol** CAS No.: 104-76-7 EC No.: 203-234-3

**Results of PBT and vPvB assessment:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**toluene** CAS No.: 108-88-3 EC No.: 203-625-9

**Results of PBT and vPvB assessment:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

**phenol** CAS No.: 108-95-2 EC No.: 203-632-7

**Results of PBT and vPvB assessment:** This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The above statement applies to the substances contained in the product from 0.1%.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The above statement applies to the substances contained in the product from 0.1%.

### 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### \* 13.1. Waste treatment methods

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

#### 13.1.1. Product/Packaging disposal

#### Waste codes/waste designations according to EWC/AVV

##### Waste code packaging

15 01 10 *	packaging containing residues of or contaminated by dangerous substances
------------	--

\*: Evidence for disposal must be provided.

#### Waste treatment options

##### Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

##### Appropriate disposal / Package:

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 14/17

## Mabanol Cut Lub 15

### SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
<b>14.1. UN number or ID number</b>			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
<b>14.2. UN proper shipping name</b>			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
<b>14.3. Transport hazard class(es)</b>			
not relevant	not relevant	not relevant	not relevant
<b>14.4. Packing group</b>			
not relevant	not relevant	not relevant	not relevant
<b>14.5. Environmental hazards</b>			
not relevant	not relevant	not relevant	not relevant
<b>14.6. Special precautions for user</b>			
not relevant	not relevant	not relevant	not relevant

#### 14.7. Maritime transport in bulk according to IMO instruments

not relevant.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU legislation

###### Restrictions on use:

Use restriction according to REACH annex XVII, no.: 3. 75.

###### Other regulations (EU):

This product is not assigned to a hazard category.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]: No information available.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds: No information available.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: Not subject to the SEVESO III directive.

Observe in addition any national regulations!

##### 15.1.2. National regulations

###### [DE] National regulations

###### Restrictions of occupation

To follow: § 22 JArbSchG.

###### Störfallverordnung (12. BlmschV)

###### for substances contained in the product:

This product is not assigned to a hazard category.

###### Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

###### Klasse 1:

5.2.5: organic substances, to be indicated as total carbon at  $m \geq 0.50$  kg/h: conc. 50 mg/m<sup>3</sup>.

###### Anteil 1:

99 %

###### Water hazard class

###### WGK:

1 - slightly hazardous to water

###### Remark:

Self-classification (mixture; calculation rule).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 15/17

## Mabanol Cut Lub 15

### 15.2. Chemical Safety Assessment

not applicable.

### 15.3. Additional information

Regulation (EU) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals: not relevant.

Water hazard class (WGK): 1 (slightly hazardous to water).

## SECTION 16: Other information

### \* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
1.4.	Emergency telephone number
2.2.	Label elements
3.2.	Mixtures
4.1.	Description of first aid measures
8.1.	Control parameters
8.3.	Additional information
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.3.	Bioaccumulative potential
13.1.	Waste treatment methods
14.3.	Transport hazard class(es)
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
16.1.	Indication of changes

### 16.2. Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: Accord européen sur le transport des marchandises dangereuses par Route (International Carriage of Dangerous Goods by Road)

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC<sub>50</sub>: Lethal concentration, 50 percent

LD<sub>50</sub>: Lethal dose, 50 percent

NIOSH: National Institute of Occupational Safety and Health

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OEL: Occupational Exposure limit (Arbeitsplatzgrenzwert)

OSHA: Occupational Safety and Health Administration

PEL: permissible exposure limit (Zulässiger Expositionsgrenzwert)

PBT: persistent bioaccumulative toxic

PNEC: predicted no effect concentration

REL: Recommended exposure limit (Empfohlene Expositionsgrenze)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 27 Aug 2025

Print date: 27 Aug 2025

Version: 5



Page 16/17

## Mabanol Cut Lub 15

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit (Kurzeitgrenzwert) (15 min)

SVHC: substance of very high concern

TLV: Threshold Limit Values (Schwellwert Grenzwerte)

TRGS Technische Regeln für Gefahrstoffe

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average (Zeitlich gewichteter Mittelwert) (8 h)

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe

WGK: Wassergefährdungsklasse

### 16.3. Key literature references and sources for data

No data available

### 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard ( <i>Asp. Tox. 1</i> )	H304: May be fatal if swallowed and enters airways.	

### 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H341	Suspected of causing genetic defects.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### 16.6. Training advice

No data available

### 16.7. Additional information

Classification according to Regulation (EC) No 1272/2008 [CLP] - Classification procedure:

health hazards: Calculation method.

Environmental hazards: Calculation method.

Physical hazards: On basis of test data.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

**Revision date:** 27 Aug 2025

**Print date:** 27 Aug 2025

**Version:** 5



Page 17/17

## Mabanol Cut Lub 15

case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

\* Data changed compared with the previous version.