

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 1/10



Mabanol Cut Lub 32

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Mabanol Cut Lub 32

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Metalworking fluids

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Mabanol GmbH & Co. KG

Koreastraße 7

20457 Hamburg

Germany

Telephone: 0049 (0) 40 36809988

E-mail: info@mabanol.com

Website: www.mabanol.com

1.4. Emergency telephone number

Giftinformationszentrale Göttingen , 24h: 0049 (0) 551 1 92 40

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word: Danger

Hazard components for labelling:

2-diethylaminoethanol; 2,2'-(octadec-9-enylimino)bisethanol; Phosphoric acid, isotridecyl ester; Alkohole, C16-18 und C18-ungesät., ethoxyliert

Supplemental hazard information

EUH210 Safety data sheet available on request.

Additional information:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. This mixture contains no substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH.

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Additional information:

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 2/10



Mabanol Cut Lub 32

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-56-9 EC No.: 265-159-2 REACH No.: 01-2119480132-48	Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9) Asp. Tox. 1 H304	29 - ≤ 48.5 weight-%
CAS No.: 100-37-8 EC No.: 202-845-2	2-diethylaminoethanol Acute Tox. 3, Acute Tox. 4, Eye Dam. 1, Flam. Liq. 3, STOT SE 3, Skin Corr. 1B H226-H302-H311-H314-H318-H331-H335	0 - ≤ 0.45 weight-%
CAS No.: 25307-17-9 EC No.: 246-807-3 REACH No.: 01-2119510876-35	2,2'-(octadec-9-enylimino)bisethanol Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1, Skin Corr. 1B H302-H314-H400-H410	0 - ≤ 0.45 weight-%
CAS No.: 52933-07-0 EC No.: 258-261-3	Phosphoric acid, isotridecyl ester Eye Dam. 1, Skin Irrit. 2 H315-H318	0 - ≤ 0.45 weight-%
CAS No.: 68920-66-1 EC No.: 500-236-9 REACH No.: 01-2119489407-26	Alkohole, C16-18 und C18-ungesät., ethoxyliert Eye Dam. 1, Skin Irrit. 2 H315-H318	0 - ≤ 0.15 weight-%
CAS No.: 7664-38-2 EC No.: 231-633-2	orthophosphoric acid Met. Corr. 1, Skin Corr. 1B H290-H314	0 - ≤ 0.09 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing.

After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion:

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Observe risk of aspiration if vomiting occurs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 3/10



Mabanol Cut Lub 32

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam. Extinguishing powder. Carbon dioxide (CO₂). Sand.

In case of major fire and large quantities: Water spray jet Water mist.

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO₂). Sulphur dioxide (SO₂).

Nitrogen oxides (NO_x).

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Ventilate affected area. Special danger of slipping by leaking/spilling product.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

For cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

* 7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8). Avoid: generation/formation of aerosols. Generation/formation of mist.

Fire prevent measures:

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.

Fire class: B (Fires of liquids or liquid turning substances).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 4/10



Mabanol Cut Lub 32

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin. Wash hands before breaks and after work. Apply skin care products after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Used working clothes should not be worn outside the work area. Wash contaminated clothing before reuse.

* 7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on storage assembly:

Do not store together with: Food and feedingstuffs.

Keep away from: Oxidizing agent.

Storage class: 10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Recommended storage temperature: 5 - 40°C

Protect against: Frost. Heat. UV-radiation/sunlight. Water. Humidity.

storage stability. ~ 24 month(s).

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

No data available

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	PNEC Value	① PNEC type
Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9) CAS No.: 64742-56-9	9.33 mg/kg	① PNEC secondary poisoning

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation.

8.2.2. Personal protection equipment



Eye/face protection:

Eye glasses with side protection (DIN EN 166).

Skin protection:

Tested protective gloves must be worn(EN ISO 374).

Suitable material: NBR (Nitrile rubber). FKM (fluoro rubber). Neoprene.

Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable protective clothing: flame-resistant.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 5/10



Mabanol Cut Lub 32

Respiratory protection:

Usually no personal respiratory protection necessary.

Respiratory protection necessary at: exceeding exposure limit values. aerosol or mist formation. Suitable respiratory protection apparatus: Filtering device (full mask or mouthpiece) with filter: A2, P2, A2/P2, ABEK.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

8.2.3. Environmental exposure controls

No data available

* 8.3. Additional information

air limit values:

Possibility of exposure to Aerosols (Mineral oil)

Limit value (TLV-TWA) = 5 mg/m³ (Source: ACGIH)

Limit value (TLV-STEL) = 10 mg/m³ (Source: ACGIH)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: not determined

Odour: not determined

Safety relevant basis data

parameter		at °C	Method	Remark
pH	<i>not determined</i>			
Melting point	<i>not determined</i>			
Freezing point	<i>not determined</i>			
Initial boiling point and boiling range	<i>not determined</i>			
Decomposition temperature	<i>not determined</i>			
Flash point	159 °C			
Evaporation rate	<i>not determined</i>			
Auto-ignition temperature	<i>not determined</i>			
Upper/lower flammability or explosive limits	<i>not determined</i>			
Vapour pressure	<i>not determined</i>			
Vapour density	<i>not determined</i>			
Density	0.879 g/cm ³	15 °C		
Bulk density	<i>not determined</i>			
Water solubility	<i>not determined</i>			
Partition coefficient: n-octanol/water	<i>not determined</i>			
Dynamic viscosity	<i>not determined</i>			
Kinematic viscosity	34.6 mm ² /s	40 °C		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 6/10



Mabanol Cut Lub 32

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

CAS No.	Substance name	Toxicological information
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)	LD₅₀ oral: >5,000 mg/kg (Rat) LD₅₀ dermal: >5,000 mg/kg (Rabbit) LC₅₀ Acute inhalation toxicity (vapour): >5.53 mg/l 4 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

Frequently or prolonged contact with skin may cause dermal irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 7/10



Mabanol Cut Lub 32

SECTION 12: Ecological information

12.1. Toxicity

CAS No.	Substance name	Toxicological information
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)	LC₅₀ : >100 mg/l 4 d (fish, Pimephales promelas (fathead minnow)) ErC₅₀ : >100 mg/l 3 d (Algae/water plant, Pseudo kirchneriella subcapitata) EC₅₀ : >10,000 mg/l 2 d (crustaceans, Daphnia magna (Big water flea)) NOEC : 10 mg/l 21 d (crustaceans, Daphnia magna (Big water flea))

12.2. Persistence and degradability

CAS No.	Substance name	Biodegradation	Remark
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)	—	Not readily biodegradable (according to OECD criteria)

Additional information:

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

12.3. Bioaccumulative potential

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

CAS No.	Substance name	Results of PBT and vPvB assessment
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)	The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

* 13.1. Waste treatment methods

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code packaging:

15 01 10 *	packaging containing residues of or contaminated by dangerous substances
------------	--

*: Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 8/10



Mabanol Cut Lub 32

SECTION 14: Transport information

No dangerous good in sense of these transport regulations.

14.1. UN-No.

not relevant

14.2. UN proper shipping name

not relevant

14.3. Transport hazard class(es)

not relevant

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

not relevant

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**15.1.1. EU legislation****Restrictions on use:**

Use restriction according to REACH annex XVII, no.: 28: Distillates (petroleum), solvent-dewaxed light paraffinic (CAS: 64742-56-9)

Other regulations (EU):

Directive 2010/75/EU on industrial emissions: No information available.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds: No information available.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: This product is not classified according to Directive 2012/18/EU.

Observe in addition any national regulations!

15.1.2. National regulations **[DE] National regulations****Störfallverordnung****Remark:**

Not subject to StörfallVO.

Technische Anleitung Luft (TA-Luft)**Remark:**

No information available.

Water hazard class (WGK)**WGK:**

1 - schwach wassergefährdend

Remark:

Self-classification (mixture; calculation rule).

15.2. Chemical Safety Assessment

not applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 9/10



Mabanol Cut Lub 32

SECTION 16: Other information

16.1. Indication of changes

1.1.	Product identifier
2.2.	Label elements
7.1.	Precautions for safe handling
7.2.	Conditions for safe storage, including any incompatibilities
8.1.	Control parameters
8.3.	Additional information
13.1.	Waste treatment methods

16.2. Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: Accord européen sur le transport des marchandises dangereuses par Route (International Carriage of Dangerous Goods by Road)

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute of Occupational Safety and Health

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OEL: Occupational Exposure limit (Arbeitsplatzgrenzwert)

OSHA: Occupational Safety and Health Administration

PEL: permissible exposure limit (Zulässiger Expositionsgrenzwert)

PBT: persistent bioaccumulative toxic

PNEC: predicted no effect concentration

REL: Recommended exposure limit (Empfohlene Expositionsgrenze)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit (Kurzzeitgrenzwert) (15 min)

SVHC: substance of very high concern

TLV: Threshold Limit Values (Schwellwert Grenzwerte)

TRGS Technische Regeln für Gefahrstoffe

TSCA: Toxic Substances Control Act

TWA: Time Weighted Average (Zeitlich gewichteter Mittelwert) (8 h)

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe

WGK: Wassergefährdungsklasse

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 May 2020

Print date: 7 May 2020

Version: 2

Page 10/10



Mabanol Cut Lub 32

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version