according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 1/11



Mabanol Cut Syn 46

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Mabanol Cut Syn 46

UFI:

F1XS-M419-TVFH-1Y4A

1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Metalworking fluids

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Mabanol GmbH & Co. KG

Koreastraße 7 20457 Hamburg Germany

Telephone: 0049 (0) 40 36809988 E-mail: info@mabanol.com Website: www.mabanol.com

E-mail (competent person): giznord@giz-nord.de

1.4. Emergency telephone number

Giftinformationszentrale Göttingen , 24h: 0049 (0) 551 1 92 40

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.	
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.	
Serious eye damage/eye irritation (Eye Dam. 1)	H318: Causes serious eye damage.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms:







GHS07 Exclamation mark

Signal word: Danger

Hazard components for labelling:

1,2-benzisothiazol-3(2H)-one; dicyclohexylamine; 2-phenoxyethanol; phosphoric acid; 2-aminoethanol

Hazard statements for health hazards		
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 2/11



Mabanol Cut Syn 46

Hazard statements	for health hazards
H318	Causes serious eye damage.

Precautionary statements Prevention		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.	
P264	Wash hands thoroughly after handling.	
P280	Wear protective gloves/protective clothing and eye/face protection.	

Precautionary statements Response		
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.	
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/	

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Description:

Mixture of substances listed below and other non-classified substances.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 39464-70-5 REACH No.: 01-2120771013-65	2-phenoxyethanol; phosphoric acid Eye Dam. 1 (H318), Skin Irrit. 2 (H315) Danger	3 – < 5 weight-%
CAS No.: 141-43-5 EC No.: 205-483-3 REACH No.: 01-2119486455-28	2-aminoethanol Acute Tox. 4 (H302, H312, H332), Aquatic Chronic 3 (H412), Eye Dam. 1 (H318), STOT SE 3 (H335), Skin Corr. 1B (H314)	3 - < 5 weight-%
CAS No.: 101-83-7 EC No.: 202-980-7 REACH No.: 01-2119493354-33	dicyclohexylamine Acute Tox. 3 (H301, H311), Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410), Eye Dam. 1 (H318), Skin Corr. 1B (H314) Danger	< 2 weight-%
CAS No.: 2634-33-5 EC No.: 220-120-9 Index No.: 613-088-00-6 REACH No.: 01-2120761540-60	1,2-benzisothiazol-3(2H)-one Acute Tox. 4 (H302), Aquatic Acute 1 (H400), Eye Dam. 1 (H318), Skin Irrit. 2 (H315), Skin Sens. 1 (H317) Danger Specific concentration limit (SCL) Skin Sens. 1; H317: C ≥ 0.05%	0.25 - < 0.5 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

Remove victim out of the danger area. When in doubt or if symptoms are observed, get medical advice.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. In case of respiratory tract irritation, consult a physician.

In case of skin contact:

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 3/11



Mabanol Cut Syn 46

After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

Following ingestion:

Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps. Where appropriate artificial ventilation. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment neededFirst Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. Water mist. Water spray jet.

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous combustion products:

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Remove persons to safety. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Ventilate affected area. Special danger of slipping by leaking/spilling product.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Cover drains. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For cleaning up:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 4/11



Mabanol Cut Syn 46

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8). Use only in well-ventilated areas. Handle and open container with care. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray. Special danger of slipping by leaking/spilling product.

Fire prevent measures:

Usual measures for fire prevention.

Keep away from sources of ignition - No smoking.

Environmental precautions:

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin. Wash hands before breaks and after work. Apply skin care products after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Used working clothes should not be worn outside the work area. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product. Protect containers against damage.

Hints on storage assembly:

Do not store together with: Food and feedingstuffs.

Keep away from: Oxidizing agent.

Storage class (TRGS 510, Germany): 10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Recommended storage temperature: 5 - 40 °C. Protect against: Heat. Frost. UV-radiation/sunlight.

storage stability: max. 12 month(s).

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
IOELV (EU)	2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	 ① 1 ppm (2.5 mg/m³) ② 3 ppm (7.6 mg/m³) ⑤ (may be absorbed through the skin)
TRGS 900 (DE) from 4 Nov 2016	2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	① 0.2 ppm (0.5 mg/m³) ② 0.2 ppm (0.5 mg/m³) ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden) DFG, EU, Y, Sh, H, 11

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 5/11



Mabanol Cut Syn 46

Limit value type (country of origin)		 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
TRGS 900 (DE)	dicyclohexylamine CAS No.: 101-83-7 EC No.: 202-980-7	 0.7 ppm (5 mg/m³) 1.4 ppm (10 mg/m³) (Aerosol und Dampf, kann über die Haut aufgenommen werden) AGS, H, Y, 11

8.1.2. Biological limit valuesNo data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type
		② Exposure route
2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	3.3 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	1 mg/kg	① DNEL worker ② Long-term - dermal, systemic effects
dicyclohexylamine CAS No.: 101-83-7 EC No.: 202-980-7	0.353 mg/m ³	① DNEL worker ② Long-term – inhalation, systemic effects
dicyclohexylamine CAS No.: 101-83-7 EC No.: 202-980-7	0.1 mg/kg	DNEL worker Long-term - dermal, systemic effects

Substance name	PNEC Value	① PNEC type
2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	0.085 mg/L	① PNEC aquatic, freshwater
2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	0.0085 mg/L	① PNEC aquatic, marine water
2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	100 mg/L	① PNEC sewage treatment plant
2-aminoethanol CAS No.: 141-43-5 EC No.: 205-483-3	0.425 mg/kg	① PNEC sediment, freshwater
dicyclohexylamine CAS No.: 101-83-7 EC No.: 202-980-7	0.00032 mg/L	① PNEC aquatic, freshwater
dicyclohexylamine CAS No.: 101-83-7 EC No.: 202-980-7	0.00003 mg/L	① PNEC aquatic, marine water
dicyclohexylamine CAS No.: 101-83-7 EC No.: 202-980-7	108 mg/L	① PNEC sewage treatment plant
dicyclohexylamine CAS No.: 101-83-7 EC No.: 202-980-7	0.00529 mg/ kg	① PNEC sediment, freshwater

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 6/11



Mabanol Cut Syn 46

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection (EN 166).

Skin protection:

Tested protective gloves must be worn (EN ISO 374).

Wearing time with permanent contact:

Suitable material: NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber). Thickness of the glove material: 0,70 mm. Breakthrough time:: > 480 min.

Wearing time with occasional contact (splashes):

Suitable material: NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber). Thickness of the glove material: 0,40 mm. Breakthrough time:: > 30 min.

Unsuitable material: PVA (Polyvinyl alcohol).

Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable protective clothing: Not readily flammable.

Respiratory protection:

Usually no personal respirative protection necessary.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Suitable respiratory protection apparatus: Combination filtering device.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid Colour: yellow

Odour: not determined

Safety relevant basis data

Parameter	Value	at °C	① Method
			② Remark
pH	9.5	20 °C	① DIN 51369
			② 5 weight-%
Melting point	not determined		
Freezing point	not determined		
Initial boiling point and boiling range	not determined		
Decomposition temperature	not determined		
Flash point	> 100 °C		① EN ISO 2592
Evaporation rate	not determined		
Auto-ignition temperature	not determined		
Upper/lower flammability or explosive limits	not determined		
Vapour pressure	not determined		
Vapour density	not determined		
Density	1.085 g/cm³	15 °C	① DIN EN ISO 12185

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 7/11



Mabanol Cut Syn 46

Parameter	Value	at °C	① Method ② Remark
Relative density	not determined		
Bulk density	not determined		
Water solubility	miscible	20 °C	
Partition coefficient: n-octanol/water	not determined		
Dynamic viscosity	not determined		
Kinematic viscosity	≈ 65 mm²/s	20 °C	① EN ISO 3104

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute oral toxicity:

No data available. The statement is derived from the properties of the single components.

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

irritant.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory or skin sensitisation:

May cause sensitization by skin contact.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 8/11



Mabanol Cut Syn 46

Aspiration hazard:

Based on available data, the classification criteria are not met.

For viscosity data, see section 9.

Additional information:

Processing vapours can irritate the respiratory tracts, skin and eyes.

11.2. Information on other hazards

Endocrine disrupting properties:

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity:

Harmless to aquatic organisms up to the tested concentration.

Additional ecotoxicological information:

There are no data available on the mixture itself. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Do not allow uncontrolled discharge of product into the environment.

12.2. Persistence and degradability

Biodegradation:

Part of the components is biodegradable.

12.3. Bioaccumulative potential

Accumulation / Evaluation:

There are no data available on the mixture itself.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV Waste code product

12 01 10 * synthetic machining oils

*: Evidence for disposal must be provided.

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Handle contaminated packages in the same way as the substance itself. Non-contaminated packages may be recycled.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 9/11



Mabanol Cut Syn 46

SECTION 14: Transport information

Land transport (ADR/RID)	(ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)	
14.1. UN number or ID number				
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	
14.2. UN proper shipping name				
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	
14.3. Transport hazard class(es)				
not relevant	not relevant	not relevant	not relevant	
14.4. Packing group				
not relevant	not relevant	not relevant	not relevant	
14.5. Environmental hazards				
not relevant	not relevant	not relevant	not relevant	
14.6. Special precautions for user				
not relevant	not relevant	not relevant	not relevant	

14.7. Maritime transport in bulk according to IMO instruments not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: This product is not assigned to a hazard category.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]: No information available. Directive 2004/42/EC on the limitation of emissions of volatile organic compounds: No information available.

Observe in addition any national regulations!

15.1.2. National regulations

[DE] National regulations

Störfallverordnung (12. BlmschV)

for substances contained in the product:

This product is not assigned to a hazard category.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:

Weight fraction (Number 5.2.5. I): <5 %. No flammable liquid according to BetrSichV.

Water hazard class

WGK:

2 - deutlich wassergefährdend

Remark:

Self-classification (mixture; calculation rule).

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

The product complies with the restrictions of the Technical Rule for Hazardous Substances (TRGS 611).

15.2. Chemical Safety Assessment

No information available.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 10/11



Mabanol Cut Syn 46

15.3. Additional information

Water hazard class (WGK): 2 (obviously hazardous to water).

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: Accord européen sur le transport des marchandises dangereuses par Route (International Carriage of Dangerous Goods by Road)

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS Chemical Abstracts Service DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC₅₀: Lethal concentration, 50 percent

LD₅₀: Lethal dose, 50 percent

NIOSH: National Institute of Occupational Safety and Health

NOAEL: No observed adverse effect level NOAEC: No observed adverse effect level

NTP: National Toxicology Program N/A: not applicable

OEL: Occupational Exposure imit (Arbeitsplatzgrenzwert) OSHA: Occupational Safety and Health Administration

PEL: permissible exposure limit (Zulässiger Expositionsgrenzwert)

PBT: persistent bioaccumulative toxic PNEC: predicted no effect concentration

REL: Recommended exposure limit (Empfohlene Expositionsgrenze)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit (Kurzzeitgrenzwert) (15 min)

SVHC: substance of very high concern

TLV: Threshold Limit Values (Schwellwert Grenzwerte)

TRGS Technische Regeln für Gefahrstoffe TSCA: Toxic Substances Control Act

TWA: Time Weighted Average (Zeitlich gewichteter Mittelwert) (8 h)

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe

WGK: Wassergefährdungsklasse

16.3. Key literature references and sources for data

No data available

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 13 Apr 2023 Print date: 13 Apr 2023

Version: 1 Page 11/11



Mabanol Cut Syn 46

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

eguiation (10, 110 11, 1, 1000 [e1.]			
Hazard classes and hazard categories	Hazard statements	Classification procedure	
Respiratory or skin sensitisation (Skin Sens. 1)	H317: May cause an allergic skin reaction.		
Skin corrosion/irritation (Skin Irrit. 2)	H315: Causes skin irritation.		
Serious eye damage/eye irritation (Eye Dam. 1)	H318: Causes serious eye damage.		

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.