

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 1/13

Mabanol Stamp 92 ASR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Mabanol Stamp 92 ASR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Metalworking fluids

* 1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Mabanol GmbH & Co. KG

Am Strandkai 1

20457 Hamburg

Germany

Telephone: 0049 (0) 40 36809988

E-mail: info@mabanol.com

Website: www.mabanol.com

E-mail (competent person): giznord@giz-nord.de

* 1.4. Emergency telephone number

Giftinformationszentrale Göttingen , 24h: 0049 (0) 551 1 92 40

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard components for labelling:

Distillates (petroleum), hydrotreated light naphthenic

Hazard statements for environmental hazards	
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements Prevention	
P273	Avoid release to the environment.

Additional information:

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Description:

Mixture of base oils and additives.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 2/13

Mabanol Stamp 92 ASR

Additional information:

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-53-6 EC No.: 265-156-6 REACH No.: 01-2119480375-34	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1 (H304) Danger Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) > 5.53 mg/L	10 - < 15 weight-%
CAS No.: 3913-02-8 EC No.: 223-470-0 REACH No.: 01-2119978234-31	2-butyl octan-1-ol Aquatic Acute 1 (H400), Aquatic Chronic 2 (H411) Warning Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg	1 - < 5 weight-%
CAS No.: 10254-57-6 EC No.: 233-593-1	4,4'-methylene bis(dibutyldithiocarbamate) Aquatic Chronic 4 (H413)	1 - < 5 weight-%
CAS No.: 68411-46-1 EC No.: 270-128-1 REACH No.: 01-2119491299-23	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene Aquatic Chronic 3 (H412), Repr. 2 (H361f) Warning Acute Toxicity Estimate ATE (oral) > 5,000 mg/kg ATE (dermal) > 2,000 mg/kg	0.5 - < 1 weight-%
CAS No.: 68920-66-1 EC No.: 500-236-9 REACH No.: 01-2119489407-26	Alcohols, C16-18 and C18-unsatd., ethoxylated Aquatic Acute 1 (H400), Skin Irrit. 2 (H315) Warning Acute Toxicity Estimate ATE (oral) > 2,000 mg/kg ATE (dermal) > 2,000 mg/kg ATE (inhalation, vapour) > 1.6 mg/L	0.5 - < 1 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. Where appropriate artificial ventilation. In case of respiratory tract irritation, consult a physician.

In case of skin contact:

Change contaminated, saturated clothing. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact:

Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

Following ingestion:

Do NOT induce vomiting. Call a physician immediately. Rinse mouth thoroughly with water. Where appropriate artificial ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 3/13

Mabanol Stamp 92 ASR

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam. Extinguishing powder. Carbon dioxide (CO₂). Water spray. Water mist.

Unsuitable extinguishing media:

Full water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Hazardous combustion products:

In case of fire: Gases/vapours, toxic.

In case of fire may be liberated: Nitrogen oxides (NO_x). Carbon monoxide. Carbon dioxide (CO₂). Sulphur oxides.

5.3. Advice for firefighters

Do not inhale explosion and combustion gases. Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Avoid contact with skin, eyes and clothes. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Ventilate affected area. Keep away from sources of ignition - No smoking.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Clear spills immediately. Wipe up with absorbent material (eg. cloth, fleece). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal. Ventilate affected area. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 4/13

Mabanol Stamp 92 ASR

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8). Use only in well-ventilated areas. Put lids on containers immediately after use. Avoid contact with skin, eyes and clothes. Do not breathe gas/fumes/vapour/spray. Use only antistatically equipped (spark-free) tools.

Fire prevent measures:

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Take precautionary measures against static discharges. Keep away from sources of ignition - No smoking.

Environmental precautions:

Do not empty into drains. Do not allow to enter into soil/subsoil. Shafts and sewers must be protected from entry of the product.

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin. Wash hands before breaks and after work. Apply skin care products after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Used working clothes should not be worn outside the work area. Wash contaminated clothing before reuse.

* 7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Only use containers specifically approved for the substance/product.

Requirements for storage rooms and vessels:

Ensure adequate ventilation of the storage area. Protect containers against damage. Floors should be impervious, resistant to liquids and easy to clean. Provide earthing of containers, equipment, pumps and ventilation facilities.

Hints on storage assembly:

Keep away from: Oxidizing agent.

Do not store together with: Food and feedingstuffs.

Storage class (TRGS 510, Germany): 10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Recommended storage temperature: 5 - 40°C.

Protect against: Frost. Heat. UV-radiation/sunlight. Humidity. Water.

Maximum storage period (time): max. 24 month(s).

7.3. Specific end use(s)

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 5/13

Mabanol Stamp 92 ASR

SECTION 8: Exposure controls/personal protection

* 8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE) from 23 Jun 2022	4,4'-methylene bis(dibutyldithiocarbamate) CAS No.: 10254-57-6 EC No.: 233-593-1	① 5 mg/m ³ ② 20 mg/m ³ ⑤ (alveolengängige Fraktion) DFG
TRGS 900 (DE) from 23 Jun 2022	4,4'-methylene bis(dibutyldithiocarbamate) CAS No.: 10254-57-6 EC No.: 233-593-1	① 20 mg/m ³ ② 160 mg/m ³ ⑤ (einatembare Fraktion) DFG

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route ③ Exposure time
Distillates (petroleum), hydrotreated light naphthenic CAS No.: 64742-53-6 EC No.: 265-156-6	5.4 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects ③ 8 h
Distillates (petroleum), hydrotreated light naphthenic CAS No.: 64742-53-6 EC No.: 265-156-6	1.2 mg/m ³	① DNEL Consumer ② Long-term - inhalation, local effects ③ 24 h
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.8 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.31 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.22 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.44 mg/kg bw/day	① DNEL Consumer ② Long-term - dermal, systemic effects
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.05 mg/kg bw/day	① DNEL Consumer ② Long-term - oral, systemic effects
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	87 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 6/13

Mabanol Stamp 92 ASR

Substance name	DNEL value	① DNEL type ② Exposure route ③ Exposure time
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	294 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	2,080 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Substance name	PNEC Value	① PNEC type
Distillates (petroleum), hydrotreated light naphthenic CAS No.: 64742-53-6 EC No.: 265-156-6	9.33 mg/kg	① PNEC secondary poisoning
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.034 mg/L	① PNEC aquatic, freshwater
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.003 mg/L	① PNEC aquatic, marine water
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	10 mg/L	① PNEC sewage treatment plant
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.446 mg/kg	① PNEC sediment, freshwater
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.045 mg/kg	① PNEC sediment, marine water
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	17.6 mg/kg	① PNEC soil
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1	0.8333 mg/kg	① PNEC secondary poisoning
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	0.002 mg/L	① PNEC aquatic, freshwater
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	0.002 mg/L	① PNEC aquatic, marine water
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	10,000 mg/L	① PNEC sewage treatment plant
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	6.33 mg/kg	① PNEC sediment, freshwater

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 7/13

Mabanol Stamp 92 ASR

Substance name	PNEC Value	① PNEC type
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9	6.33 mg/kg	① PNEC sediment, marine water

* 8.2. Exposure controls

8.2.1. Appropriate engineering controls

Use only in well-ventilated areas. If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Technical measures and the application of suitable work processes have priority over personal protection equipment.

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection (EN 166).

Skin protection:

Tested protective gloves must be worn (EN ISO 374).

Wearing time with permanent contact:

Suitable material: NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber). PVA (Polyvinyl alcohol). Thickness of the glove material: 0,40 mm. Breakthrough time:: > 480 min.

Wearing time with occasional contact (splashes):

Suitable material: NBR (Nitrile rubber). CR (polychloroprene, chloroprene rubber). PVA (Polyvinyl alcohol). Thickness of the glove material: 0,40 mm. Breakthrough time:: > 30 min.

Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable protective clothing:: flame-resistant.

Respiratory protection:

Usually no personal respirative protection necessary.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection necessary at: exceeding exposure limit values. insufficient ventilation. aerosol or mist formation.

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

* 9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: brown

Odour: not determined

flammability: No data available

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	No data available		
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	> 200 °C		② 1013 hPa
Flash point	150 °C		① EN ISO 2592
Evaporation rate	No data available		
Auto-ignition temperature	> 200 °C		
Upper/lower flammability or explosive limits	No data available		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 8/13

Mabanol Stamp 92 ASR

Parameter	Value	at °C	① Method ② Remark
Vapour pressure	No data available		
Vapour density	No data available		
Density	1.008 g/cm ³	15 °C	① DIN EN ISO 12185
Bulk density	not applicable		
Water solubility	practically insoluble	20 °C	
Dynamic viscosity	No data available		
Kinematic viscosity	≈ 92 mm ² /s	40 °C	① EN ISO 3104

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapours.

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Distillates (petroleum), hydrotreated light naphthenic CAS No.: 64742-53-6 EC No.: 265-156-6
LD₅₀ oral: >5,000 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (vapour): >5.53 mg/L 4 h (Rat)
2-butyloctan-1-ol CAS No.: 3913-02-8 EC No.: 223-470-0
LD₅₀ oral: >5,000 mg/kg (Rat) OECD 401
LD₅₀ dermal: >2,000 mg/kg (Rabbit)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1
LD₅₀ oral: >5,000 mg/kg (Rat) OECD 401
LD₅₀ dermal: >2,000 mg/kg (Rat) OECD 402
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9
LD₅₀ oral: >2,000 mg/kg (Rat) OECD 401
LD₅₀ dermal: >2,000 mg/kg (Rabbit) OECD 402
LC₅₀ Acute inhalation toxicity (vapour): >1.6 mg/L 4 h (Rat) OECD 403

Acute oral toxicity:

No data available. The statement is derived from the properties of the single components.
Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 9/13

Mabanol Stamp 92 ASR

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

For viscosity data, see section 9.

Additional information:

Frequently or prolonged contact with skin may cause dermal irritation.

11.2. Information on other hazards

Endocrine disrupting properties:

No information available.

SECTION 12: Ecological information

* 12.1. Toxicity

Distillates (petroleum), hydrotreated light naphthenic CAS No.: 64742-53-6 EC No.: 265-156-6
EC₅₀: >10,000 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
NOEC: >10 mg/L 21 d (crustaceans, Daphnia magna (Big water flea))
LC₅₀: >100 mg/L 4 d (fish, Pimephales promelas (fathead minnow))
NOEC: >100 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
2-butyloctan-1-ol CAS No.: 3913-02-8 EC No.: 223-470-0
LC₅₀: >0.1 - 1 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
EC₅₀: >0.1 - 1 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
ErC₅₀: >1 - 10 mg/L 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1
LC₅₀: >100 mg/L (fish, Danio rerio (zebrafish)) OECD 203
EC₅₀: >100 mg/L (Algae/water plant, Desmodesmus subspicatus) OECD 201
EC₅₀: 51 mg/L (crustaceans, Daphnia magna (Big water flea)) OECD 202
Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9
LC₅₀: 10 - 100 mg/L 4 d (fish, Danio rerio (zebrafish)) OECD 203
EC₅₀: 51 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) OECD 202

Aquatic toxicity:

Harmful to aquatic life.

Additional ecotoxicological information:

There are no data available on the mixture itself. The ecotoxicological properties of this mixture are determined by the ecotoxicological properties of the single components (see section 3).

Do not allow uncontrolled discharge of product into the environment.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2

Page 10/13



Mabanol Stamp 92 ASR

* 12.2. Persistence and degradability

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1

Biodegradation: —

Remark: Not readily biodegradable (according to OECD criteria).
--

Abiotic degradation:

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

Biodegradation:

Part of the components is biodegradable.

* 12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated light naphthenic CAS No.: 64742-53-6 EC No.: 265-156-6

Log K_{OW}: > 3.5

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1

Log K_{OW}: 6.66

Bioconcentration factor (BCF): 4,176

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4. Mobility in soil

No information available.

* 12.5. Results of PBT and vPvB assessment

Distillates (petroleum), hydrotreated light naphthenic CAS No.: 64742-53-6 EC No.: 265-156-6

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

2-butyloctan-1-ol CAS No.: 3913-02-8 EC No.: 223-470-0

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene CAS No.: 68411-46-1 EC No.: 270-128-1

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Alcohols, C16-18 and C18-unsatd., ethoxylated CAS No.: 68920-66-1 EC No.: 500-236-9
--

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

4,4'-methylene bis(dibutyldithiocarbamate) CAS No.: 10254-57-6 EC No.: 233-593-1

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

No information available.

12.7. Other adverse effects

Damage can be caused through mechanical influence of the product (eg. sticking).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

12 01 07 *	mineral-based machining oils free of halogens (except emulsions and solutions)
------------	--

*: Evidence for disposal must be provided.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 11/13

Mabanol Stamp 92 ASR

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of. Dispose of waste according to applicable legislation.

13.2. Additional information

Never use pressure to empty container.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.2. UN proper shipping name			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es)			
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental hazards			
not relevant	not relevant	not relevant	not relevant
14.6. Special precautions for user			
not relevant	not relevant	not relevant	not relevant

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Restrictions on use:

Use restriction according to REACH annex XVII, no.: 3. 75.

Other regulations (EU):

This product is not assigned to a hazard category.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]: No information available.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds: No information available.

Observe in addition any national regulations!

15.1.2. National regulations

[DE] National regulations

Störfallverordnung (12. BImSchV)

for substances contained in the product:

This product is not assigned to a hazard category.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:

Weight fraction (Number 5.2.5. I): <5 %.

No flammable liquid according to BetrSichV.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 12/13

Mabanol Stamp 92 ASR

Water hazard class

WGK:

1 - slightly hazardous to water

Remark:

Self-classification (mixture; calculation rule).

15.2. Chemical Safety Assessment

No information available.

* 15.3. Additional information

Water hazard class (WGK): 1 (slightly hazardous to water).

SECTION 16: Other information

* 16.1. Indication of changes

1.3.	Details of the supplier of the safety data sheet
1.4.	Emergency telephone number
2.2.	Label elements
3.2.	Mixtures
7.2.	Conditions for safe storage, including any incompatibilities
8.1.	Control parameters
8.2.	Exposure controls
9.1.	Information on basic physical and chemical properties
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.2.	Persistence and degradability
12.3.	Bioaccumulative potential
12.5.	Results of PBT and vPvB assessment
14.3.	Transport hazard class(es)
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
15.3.	Additional information
16.1.	Indication of changes
16.5.	List of relevant hazard statements and/or precautionary statements from sections 2 to 15

16.2. Abbreviations and acronyms

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: Accord européen sur le transport des marchandises dangereuses par Route (International Carriage of Dangerous Goods by Road)

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC₅₀: Lethal concentration, 50 percent

LD₅₀: Lethal dose, 50 percent

NIOSH: National Institute of Occupational Safety and Health

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 9 Jan 2025

Print date: 9 Jan 2025

Version: 2



Page 13/13

Mabanol Stamp 92 ASR

OEL: Occupational Exposure limit (Arbeitsplatzgrenzwert)
OSHA: Occupational Safety and Health Administration
PEL: permissible exposure limit (Zulässiger Expositionsgrenzwert)
PBT: persistent bioaccumulative toxic
PNEC: predicted no effect concentration
REL: Recommended exposure limit (Empfohlene Expositionsgrenze)
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit (Kurzzeitgrenzwert) (15 min)
SVHC: substance of very high concern
TLV: Threshold Limit Values (Schwellwert Grenzwerte)
TRGS Technische Regeln für Gefahrstoffe
TSCA: Toxic Substances Control Act
TWA: Time Weighted Average (Zeitlich gewichteter Mittelwert) (8 h)
VOC: Volatile Organic Compounds
vPvB: very persistent and very bioaccumulative
VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe
WGK: Wassergefährdungsklasse

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
Hazardous to the aquatic environment (Aquatic Chronic 3)	H412: Harmful to aquatic life with long lasting effects.	

* 16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version.