

# Mabanol Delta 2T-M

## Two-Stroke Engine Oil

### Application

Mabanol Delta 2T-M is recommended by various manufacturers for mixing ratios of up to 1:50 and for separate lubrication (autolube systems). This two-stroke engine oil for high-performance engines is mineral-oil based.

### Specifications

- ISO L-EGB
- API TC
- JASO FB

### Properties

Mabanol Delta 2T-M is a self-mixing two-stroke motor oil. The self-mixing property ensures not only cleanliness of the pistons and protection against corrosion but also prevents ring sticking and glow ignitions. Self-ignition requirements are also fully fulfilled.

### Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,878
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	63,6
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	8,6
Viscosity Index (VI)	DIN ISO 2909		108
Flash point PM	DIN EN ISO 2719	°C	141
Pourpoint	DIN ISO 3016	°C	-24
Total base number	DIN ISO 3771	mg KOH/g	1,25

Updated in January 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981