

## Mabanol Delta 2T Synth

Fully Synthetic High Performance Two-Stroke Engine Oil

### Application

Mabanol Delta 2T Synth is recommended in accordance with manufacturer's instructions for mixing ratios of up to 1:100 and for separate lubrication (autolube systems). This two-stroke engine oil complies with the highest specifications for both the Asian and the European market.

### Properties

Mabanol Delta 2T Synth is a self-mixing, fully synthetic low ash and low-smoke two-stroke motor oil. Synthetic components and special additives ensure optimum lubrication and a high degree of engine cleanliness. The formation of deposits in the combustion chamber and the exhaust system are prevented and the formation of smoke is substantially reduced.

### Specifications

- ISO L-EGD
- API TC
- JASO FD
- TISI

### Recommended for

- Husqvarna Chainsaw
- Piaggio
- Rotax Snowmobile

### Data

	Test method	Unit	Value
Colour			amber
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,894
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	56,9
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	9,02
Viscosity Index (VI)	DIN ISO 2909		137
Flash point PM	DIN EN ISO 2719	°C	115
Pourpoint	DIN ISO 3016	°C	-42
Total base number	DIN ISO 3771	mg KOH/g	2,0

Updated in September 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 3403 1980