

Mabanol Engine Cleaner

High-performance cleaner for oil circuits of engines

Application

Mabanol Engine Cleaner is a cleaning concentrate suitable for cleaning of all types of petrol and diesel engines, either equipped with or without a catalytic converter or turbo-charger respectively. It is highly recommended for use in engines when the last oil drain interval is not specified or unknown.

Add Mabanol Engine Cleaner to the hot used oil. Idle the engine for at least 10 minutes. Afterwards drain the oil, fill the motor with the new lubricant and change the oil filter.

Properties

Mabanol Engine Cleaner is produced with low viscosity surfactants and efficiently cleans accumulated deposits and clogging which appear in the engine. These removed deposits are then drained along with the used oil during the oil drain. It reduces rattling of hydraulic tappet and compression losses around the piston rings. The cleaning of the engine brings down oil consumption and reduces wear.

EAN Code

400 ml can: 4260214892136

Data

	Test method	Unit	Value
Density at 20°C	DIN 51 757	g/cm ³	0,817
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	< 7
Flash point	ISO 3679	°C	> 100
Lower explosion limit	–	Vol-%	0,5
Upper explosion limit	–	Vol-%	8,0

Updated in March 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 3811 2100