

Mabanol Engine Coolant Premium

Silicate-Free Engine Coolant Concentrate

Application

Mabanol Engine Coolant Premium offers excellent corrosion protection in the cooling system with its vital parts, the coolant channels in the block and cylinder head, the radiator, the water pump and the heatercore. It is also suitable for coolant systems with aluminum engines. It is miscible with most ethylene-glycol based engine coolants.

Properties

Mabanol Engine Coolant Premium is a nitrite-, amine-, phosphate-, borate- and silicate-free antifreeze based on ethylene glycol.

It provides protection against corrosion, cavitation and deposits and reduces the formation of foam.

As with any antifreeze coolant, the use of galvanized steel is not recommended for pipes or any other part of the storage and mixing installation.

Recommendation: mix only with distilled water.

Recommended for

- Chrysler MS 9176
- Ford ESE M97B49-A
- Ford ESD M97B49-A
- Ford WSS-M97B44-D
- John Deere H 24 B1 und C1
- MB-Sheet 325.3
- OPEL GM QL 130100
- Renault 41-01-00
- Porsche/Audi/VW/Seat/Skoda TL 774 F
- VOLVO (Reg. NDeutz/MWN 0199-2091 2 Edition (C.W.) o 260)

Dilution table

Concentrate	Ratio	1	1	1
Water	Ratio	2	1,5	1
Frost protection	°C	-20	-26	-36

Not to be mixed to frost protection ratios higher than -17°C , since a coolant content of less than 33 % would no longer ensure optimum corrosion protection.

Data

	Unit	Value
Flash point	°C	> 111
Boiling point	°C	> 195
pH value		8 - 10

Updated in May 2025

The above values may vary within the commercial limits.

HS Code.: 3820 0000