



# Mabanol Engine Oil Additive

## Motor Oil Additive

### Application

Mabanol Engine Oil Additive is filled into the engine along with the motor oil. It is miscible with all types of motor oil.

It can be used in all petrol and diesel engines, including those equipped with catalytic converters, turbochargers and/or particulate filters both in passenger cars as well as in trucks. Not suitable for use in ATFs and motorcycles with wet clutch.

Mabanol Engine Oil Additive is also recommended for improving the performance of oil in pumps, gearboxes and compressors.

A can of 300 ml can be used for up to 4.5 liters of engine oil. The maximum dosage in the engine oil/additive blend is 20 volume percent. Please ensure that the correct oil level is maintained.

**Please shake well before use.**

### Properties

Mabanol Engine Oil Additive is a nano technology-based oil additive designed to reduce friction on mechanical parts, optimize engine performance and protect it in a durable way.

Mabanol Engine Oil Additive produces a robust lubricating film on the friction surfaces in the engine which reduces friction losses and wear. This extends the life of the engine, improves smoothness and optimizes efficiency.

### EAN Code

300 ml can: 4260214890989

### Data

	Test method	Unit	Value
Density at 20°C	DIN 51 757	g/cm <sup>3</sup>	0,874
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	316
Flash point	ISO 3679	°C	> 100
Lower explosion limit	—	Vol-%	0,6
Upper explosion limit	—	Vol-%	6,5

Updated in March 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 3811 2100

**Mabanol GmbH & Co. KG, Koreastraße 7, 20457 Hamburg, Deutschland**

Telefon +49 (0)40 36809988, Telefax +49 (0)40 36901781,

Email: [info@mabanol.com](mailto:info@mabanol.com), Internet: [www.mabanol.com](http://www.mabanol.com)