

Mabanol Gamma Rubor EP 2

Calcium-based Multipurpose Grease

Application

Mabanol Gamma Rubor EP 2 is especially developed for marine applications and as an universal grease for forestry, agricultural and construction vehicles. The product is also suited to industrial applications where water washout and corrosion are problematic. The grease is easily pumpable in most of the modern centralised lubrication systems despite of its high base oil viscosity.

Properties

Mabanol Gamma Rubor EP 2 is an anhydrous calcium-based lubricating grease based on a mixture of mineral oil and polymer. The grease contains antioxidants, corrosion inhibitors and EP/AW additives. Mabanol Gamma Rubor EP 2 offers corrosion protection, excellent water resistance, high load-carrying capacity as well as excellent adhesion.

Standards

- NLGI Grade 2
- DIN KP2K-30
- ISO: ISO-L-XC(F)CIB2

Data

	Test method	Unit	Value
Useful temperature on continuous lubrication		°C	-30 to +120
Drop point	ISO 2176	°C	>140
Worked penetration (60 strokes)	ISO 2137	1/10 mm	265 – 295
Water resistance (90°C)	DIN 51 807:1		0-90
Base oil viscosity at 40°C	ASTM D 7152	mm ² /s	1.370
Emcor salt water	ISO 11007		max 2-2

Updated in August 2016

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1999