

Mabanol Pirate Cruise 20W-50

4 Stroke Motorcycle Engine Oil

Application

Mabanol Pirate Cruise 20W-50 is an engine oil developed for use in four-stroke motorbike engines. It satisfies the technical demands of all motorcycle manufacturers, and is suitable for all air-cooled and water-cooled 4-stroke motorbike engines. The high engine cleanliness and wear protection properties afforded by this oil lengthen the engine life of the machine. Both qualities are suitable for wet clutches. Clutch grabbing and slipping from a cold start are averted.

Properties

Mabanol Pirate Cruise is a mineral oil based high-performance engine oil in the SAE 20W-50 viscosity range. Very good high-temperature stability and a high wear protection guarantee optimal lubrication security even under unfavourable conditions. The motorcycle engine is protected from deposits and oil-sludge, and oil consumption is significantly reduced.

Specifications

- SAE Grade 20W-50
- API SG
- JASO MA2

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,888
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	150
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	16,7
Viscosity Index (VI)	DIN ISO 2909		119
Flash point COC	DIN ISO 2592	°C	235
Pourpoint	DIN ISO 3016	°C	-30

Updated in August 2016

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981