

Mabanol Radiator Sealant

High Performance Radiator Sealant

Application

Mabanol Radiator Sealant is a high performance sealant designed for use in cooling systems. The product protects cooling systems against sealing damages and increases operating safety.

Mabanol Radiator Sealant is recommended for use in leaking head gaskets, leaking hose connections as well as hairline cracks in the radiator, cylinder head and engine block. It is also suitable for closed cooling systems and has no impact on rubber, plastics, alloys and non-ferrous metals.

Before using Mabanol Radiator Sealant shake the bottle. Open the heating valve completely, the engine should be at operating temperature and pour the content into the running engine's cooling system. Fill cooling water. After filling, leave engine running for a further 10 minutes or do a test drive. Check cooling water level, ventilation and system sealing. The content of a tin is suitable for 10 litres of coolant.

When used in commercial vehicles kindly consider the mixing ratio of max. 1:100. It is compatible with antifreeze products.

Properties

Mabanol Radiator Sealant ensures the permanent sealing of hairline cracks and leaks. The product prevents sealant sweating and coolant water loss. The radiator sealant should not be used when a filter is used in the cooling system.

EAN Code

300 ml can: 4260214890125

Data

	Test method	Unit	Value
Density at 20°C	DIN 51 757	g/cm ³	0,832
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	< 7
Flash point	ISO 3679	°C	62
Lower explosion limit	–	Vol-%	1,2
Upper explosion limit	–	Vol-%	8,8

Updated in April 2023

The above values may vary within the commercial limits.

Customs Tariff No.: 3824 9996