

# Mabanol Radon Gear ATF CVT

Multi-Purpose Fluid for Continuously Variable Transmissions

## Application

Mabanol Radon Gear ATF CVT is an automatic transmission fluid perfectly suited to continuously variable transmissions. It can be equally used for CVT versions equipped with pushbelts.

## Properties

Mabanol Radon Gear ATF CVT's formulation is a blend of high-quality base stocks and a matching additive package. To ensure a reliable operation, longer durability and low friction, the product offers a very good wear, corrosion and oxidation protection.

The product is not suitable for use in hybrid CVTs (Honda/Ford), DCTs (Dual Clutch Transmission) or automatic stages.

Mabanol Radon Gear ATF CVT is dyed red.

## Recommended for

- Audi Multitronic
- BMW Mini Cooper EZL799
- Daihatsu Ammix CVT DFE
- Daihatsu Ammix CVT Fluid DC / DFC
- Dodge / Jeep / Chrysler NS-2 / Mopar CVT+4
- GM / Saturn DEX-CVT
- Honda HMMF (without starting clutch) / HCF2
- Honda Z-1 (CVT model, without starting clutch, not SFU for 2001-2007 Honda Fit & Jazz)
- Hyundai / KIA SP III (CVT model)
- Idemitsu CVTS-EX1
- Mazda JWS 3320
- MB-Sheet 236.20
- Mitsubishi Diaqueen CVTF-J1 / -J4 / -J4+
- Mitsubishi Diaqueen SP-III (CVT model only)
- Nissan NS-1 / NS-2 / NS-3
- Punch CVT
- Shell Green 1V
- Subaru iCVT / iCVT FG / ECVT
- Subaru Lineartronic chain CVT and CVT II Fluid
- Subaru Lineartronic High Torque (HT) CVT Fluid
- Suzuki CVTF TC / CVTF 3320
- Suzuki NS-2 / CVT Green 1 & 2
- Toyota CVTF TC / CVTF FE
- VW TL 521 16 (G 052 516)
- VW TL 521 80 (G 052 180)

## Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm <sup>3</sup>	0,848
Dyn. Viscosity at -30°C	DIN 51 398	mPa s	8.500
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm <sup>2</sup> /s	32,6
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm <sup>2</sup> /s	6,99
Viscosity Index (VI)	DIN ISO 2909	-	183
Flash point COC	DIN EN ISO 2592	°C	212
Pourpoint	DIN ISO 3016	°C	-48

Updated in Juli 2020

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987