

Mabanol Radon Gear Eco GL 4 80W-90

Multi EP Gear Oil

Application

Mabanol Radon Gear Eco GL 4 80W-90 is a multipurpose gear oil for the use in all gear boxes (with and without synchronization, transfer gearboxes, various steering gears and normal loaded drive axles – as far as API GL 5 hypoid gear oils are not mandatory required.

Properties

Mabanol Radon Gear Eco GL 4 80W-90 is a multigrade gear oil composed of selected base oils with special carrying additives and oxidation inhibitors. The gear oil offers good low temperature behaviour and high wear protection at high temperature.

Specifications

- SAE Grade 80W-90
- API GL-4

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,890
Viscosity at -26°C	DIN 51 398	mPa s	140.000
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	140
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	14,1
Viscosity Index (VI)	DIN ISO 2909		98
Flashpoint COC	DIN ISO 2592	°C	230
Pourpoint	DIN ISO 3016	°C	-30

Updated in June 2018

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1987