

Mabanol Radon Gear XHP GL 4 75W-80

Fully Synthetic High-Performance Fuel Economy Gear Oil

Application

Mabanol Radon Gear XHP GL 4 75W-80 is a high-performance gear oil designed for use in heavily loaded manual transmissions. The fuel economy formulation significantly reduces maintenance costs and leads to increased profitability as well as oil change intervals of up to 500.000 km.

Properties

Mabanol Radon Gear XHP GL 4 75W-80 is a fully synthetic fuel-economy gear oil. Synthetic base oils coupled with an innovative additive package ensure that the latest industry requirements are fully met.

Mabanol Radon Gear XHP GL 4 75W-80 provides exceptional protection against mechanical and thermal loads even at extended oil drain intervals.

Specifications

- SAE Grade 75W-80
- API GL-4

Approvals

- MAN 341 Typ Z4

Recommended for

- DAF
- Eaton Transmission
- Iveco 18-1807 MGS1
- MAN 341 Typ E3, VR
- Renault
- Voith Oil class C
- Volvo 97305 / 97307
- ZF TE-ML 01L / 02L / 02D / 07A / 08 / 16K

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,857
Kin. Viscosity at 40°C	DIN 51562-1	mm ² /s	55
Kin. Viscosity at 100°C	DIN 51562-1	mm ² /s	9,2
Viscosity Index (VI)	DIN ISO 2909		155
Flashpoint COC	DIN ISO 2592	°C	> 200
Pourpoint	DIN ISO 3016	°C	-42

Updated in May 2023

The above values may vary within the commercial limits.

Customs Tariff No.: 3403 1980