

Mabanol Silicone Spray

High-performance silicone-based lubricant

Application

Mabanol Silicone Spray lubricates moving machine parts, especially in the vehicle and plastics manufacturing sectors as well as in the paper and printing industry.

It can be applied on a broad range of surfaces, e.g. on plastics, rubber, metals and wood. Therefore it is ideally suited for the care of dashboards, door locks, door and window seals in vehicles, especially in rather severe conditions such as a low temperature environment when improved protection for car components is imperative.

Thoroughly clean the parts or surfaces before the application, then spray evenly from a distance of about 20 cm.

Properties

Mabanol Silicone Spray is a mineral-oil and grease-free, silicone-based product containing release-, anti-slip- and protective agents.

It provides excellent protection against corrosion and is water-repellent, hence offering excellent protection against moisture and corrosion.

After spraying, Mabanol Silicone Spray leaves a thin sliding layer of silicone on the surface. Furthermore it protects rubber seals from premature aging and protects metal and chrome parts from corrosion.

Also it stops squeaking and creaking noises.

EAN Code

500 ml can: 4260214892099

Data of product in spray can

	Test method	Unit	Value
Density at 20°C	DIN 51 757	g/cm ³	0,745
Viscosity	DIN 51 550	mm ² /s	2,5

Data after solvent evaporation

	Test method	Unit	Value
Temperature range		°C	-30 to +150
Density at 20°C	DIN 51 757	g/cm ³	0,965
Viscosity	DIN 51 550	mm ² /s	350
Flash point		°C	> 120

Updated in May 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 3403 1980