

Mabanol Xenon Alpha Classic 15W-40

Universal Multigrade Engine Oil

Application

Mabanol Xenon Alpha Classic 15W-40 was developed for universal use and is suitable for mixed vehicle fleets and construction industry operations. The performance of this multigrade engine oil meets the requirements commercial and passenger car diesel engines as well as that of petrol engines with or without turbochargers.

Properties

Mabanol Xenon Alpha Classic 15W-40 is a multigrade engine oil suited for use in diesel and petrol engines. The 15W-40 viscosity range ensures good fluidity and excellent cold starts in winter and high temperature stability even under extreme loads.

High-quality base oils together with selected additives will ensure excellent anti-wear properties and engine cleanliness. The formation of black sludge will also be avoided.

Specifications

- SAE Grade 15W-40
- ACEA A3/B3
- API SL/CG-4

Recommended for

- MB-Sheet 229.1



Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,883
Dyn. Viscosity at -20°C	ASTM D 5293	mPa s	6.380
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	102
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	13,8
Viscosity Index (VI)	DIN ISO 2909		133
Flash point COC	DIN ISO 2592	°C	236
Pourpoint	DIN ISO 3016	°C	-39

Updated in March 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981