

Mabanol Xenon Alpha Stellar 10W-40

Semi-Synthetic High Performance Engine Oil

Application

Mabanol Xenon Alpha Stellar 10W-40 is recommended for all passenger car diesel and petrol engines including turbo-charged diesel and catalytic converter models.

Properties

Mabanol Xenon Alpha Stellar 10W-40 is a semi-synthetic high performance low-friction engine oil, the base oil composition of which combines the advantage of the base oil being derived from the most modern refinery technology together with high quality synthetic components. Base oil composition and very shear-stable viscosity index improvers ensure that the stated viscosity class is maintained throughout the entire oil service time.

The efficiency of this engine oil is maintained to the maximum level of requirement between engine service intervals. Antioxidants and cleaning additives prevent deposits, pistons and valves remain clean and the development of cold sludge is also prevented. Lower friction losses in the engine produce clear fuel savings and thus lower environmental impact. Lower evaporation losses prevent valve deposits and blockages and provide clean pistons and piston ring grooves.

Specifications

- SAE Grade 10W-40
- ACEA A3/B4
- API SN/CF

Recommended for

- MB-Sheet 229.1
- VW 501 01/505 00



Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,873
Dyn. Viscosity at -25°C	ASTM D 5293	mPa s	6.400
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	101
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	14,9
Viscosity Index (VI)	DIN ISO 2909		154
Flash point COC	DIN ISO 2592	°C	224
Pourpoint	DIN ISO 3016	°C	-36
Sulphated ash	DIN 51 575	g/100 g	1,3

Updated in August 2017

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981