

Mabanol Xenon Alpha Synth 10W-30

High-performance engine oil based on synthetic technology

Application

Mabanol Xenon Alpha Synth 10W-30 is a high-performance engine oil designed for use in the latest petrol-powered passenger cars, covering the requirements of turbocharged and direct-injection engines.

It can be widely used in a vast number of the latest petrol engines manufactured by Asian automakers.

Properties

Mabanol Xenon Alpha Synth 10W-30 is formulated with a blend of synthetic base oil components and a matching additive package.

Mabanol Xenon Alpha Synth 10W-30 is suitable for year-round use and is designed for extended oil drain intervals. It ensures a high level of protection against the formation of sludge and helps to ward off coking as well as corrosion in the petrol engine.

Specifications

- SAE Grade 10W-30
- API SN
- ILSAC GF-5

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm³	0,85
Dyn. Viscosity at -25°C	ASTM D 5293	mPa s	3.550
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm²/s	60,4
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm²/s	10,0
Viscosity Index (VI)	DIN ISO 2909		152
Flash point COC	DIN ISO 2592	°C	252
Pourpoint	DIN ISO 3016	°C	-39

Updated in July 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981

Email: info@mabanol.com, Internet: www.mabanol.com